

PROPEL ADVANCED SL TEAM FRAMESET*



SPECS

FRAME	
SIZES	S, M, M/L, L, XL
COLORS	Purple Storm
FRAME	Advanced SL-Grade Composite, integrated seatpost, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	N/A
GRIPS	N/A
STEM	N/A
SEATPOST	Advanced SL-Grade composite, integrated design, -5/+15mm offset
SADDLE	N/A
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	N/A
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	N/A
BRAKES	N/A
BRAKE LEVERS	N/A
CASSETTE	N/A
CHAIN	N/A
CRANKSET	N/A
BOTTOM BRACKET	BB86 accepts press fit style BB only, bearing set not included

WHEELS	
RIMS	N/A
HUBS	N/A
SPOKES	N/A
TIRES	N/A
EXTRAS	Front & rear 12mm thru-axes, 20mm & 45mm ISP clamps, Computer Mount, Bottle Cages, 30mm max tyre size
LIMITS	
MAX TIRE CLEARANCE	30 mm

Price: \$6,199.00

GEOMETRY

FRAME	XS	S	M	ML	L
Seat Tube Length (mm)	680	710	740	770	800
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	520	535	550	565	580
Head Tube Length (mm)	120	130	145	165	185
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45
Trail (mm)	70.5	62.5	57.8	57.8	57.8
Wheelbase (mm)	976	977	980	991	1006
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67
Stack (mm)	517	528	545	562	581
Reach (mm)	376	383	388	393	402
Stand Over Height (mm)	734	755	775	794	821
Stem Length (mm)	80	90	100	110	110
Crank Length (mm)	170	170	172.5	172.5	175
Wheel Size	700C	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.