



SPECS

| FRAME | |
|-------------------------|--|
| SIZES | S, M, L, XL |
| COLOURS | Airglow/Cold Night |
| FRAME | ALUXX SL-Grade Aluminium front and rear triangles, 160mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage |
| FORK | Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant |
| SHOCK | Fox Float X Performance Elite, custom tuned for Giant |
| COMPONENTS | |
| HANDLEBAR | Giant Contact SL TR35 |
| GRIPS | Giant Tactal Pro Single |
| STEM | Giant Contact SL 35 |
| SEATPOST | Giant Contact Switch dropper, remote |
| SADDLE | Giant Romero |
| PEDALS | N/A |
| DRIVETRAIN | |
| SHIFTERS | Shimano SLX SL-M7100, 1x12 |
| FRONT DERAILLEUR | N/A |
| REAR DERAILLEUR | Shimano SLX RD-M7100 |
| BRAKES | Shimano Deore BR-M6120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm |
| BRAKE LEVERS | Shimano Deore BL-M6100 |
| CASSETTE | Shimano SLX M7100, 10x51 |
| CHAIN | Shimano |
| CRANKSET | Shimano MT512, 32t, 55mm chainline |
| BOTTOM BRACKET | Shimano, press fit |

| WHEELS | |
|---------------|--|
| RIMS | Giant AM 29, alloy |
| HUBS | Alloy, sealed |
| SPOKES | Sapim |
| TIRES | [F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless |
| EXTRAS | Tubeless prepared, 2.5" max tyre size, 36t max chainring size, MRP AMG CS chain guide |

Price: \$5,699.00

GEOMETRY

| FRAME | S | | | M | | | L | | | XL | | |
|--------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | LOW | MID | HIGH | LOW | MID | HIGH | LOW | MID | HIGH | LOW | MID | HIGH |
| Seat Tube Length (mm) | 400 | | | 425 | | | 450 | | | 475 | | |
| Seat Tube Angle | 78.3° | 78.7° | 79.0° | 78.3° | 78.7° | 79.0° | 77.3° | 77.7° | 78.0° | 77.3° | 77.7° | 78.0° |
| Top Tube Length (mm) | 556 | 555 | 555 | 587 | 586 | 585 | 620 | 620 | 619 | 652 | 652 | 651 |
| Head Tube Length (mm) | 100 | | | 105 | | | 115 | | | 120 | | |
| Head Tube Angle | 63.5° | 63.9° | 64.2° | 63.5° | 63.9° | 64.2° | 63.5° | 63.9° | 64.2° | 63.5° | 63.9° | 64.2° |
| Fork Rake (mm) | 44 | | | 44 | | | 44 | | | 44 | | |
| Trail (mm) | 140 | 138 | 135 | 140 | 138 | 135 | 140 | 138 | 135 | 140 | 138 | 135 |
| Wheelbase (mm) | 1214 | 1213 | 1212 | 1246 | 1245 | 1244 | 1271 | 1270 | 1269 | 1304 | 1303 | 1302 |
| Chain Stay Length (mm) | 445 | 443 | 442 | 445 | 443 | 442 | 445 | 443 | 442 | 445 | 443 | 442 |
| Bottom Bracket Drop (mm) | 35 | 30 | 25 | 35 | 30 | 25 | 35 | 30 | 25 | 35 | 30 | 25 |
| Stack (mm) | 627 | 624 | 622 | 632 | 629 | 626 | 641 | 638 | 635 | 645 | 642 | 639 |
| Reach (mm) | 426 | 430 | 434 | 456 | 460 | 464 | 476 | 480 | 484 | 506 | 510 | 514 |
| Stand Over Height (mm) | 723 | 727 | 732 | 743 | 747 | 752 | 756 | 760 | 765 | 771 | 777 | 782 |
| Stem Length (mm) | 40 | | | 40 | | | 40 | | | 40 | | |
| Crank Length (mm) | 165 | | | 170 | | | 170 | | | 170 | | |
| Wheel Size | 29" | | | 29" | | | 29" | | | 29" | | |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.