

REIGN 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Mars Dust
FRAME	ALUXX SL-Grade Aluminium front and rear triangles, 160mm Maestro suspension, flip chip 3 position, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, integrated downtube storage, 55mm Chainline
FORK	Fox 38 Performance Elite, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
SHOCK	Fox Float X Performance Elite, 2 position, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX SL-M7100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX RD-M7100 Shadow +
BRAKES	Shimano Deore BR-M6120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]203mm
BRAKE LEVERS	Shimano Deore BL-M6100
CASSETTE	Shimano SLX M7100, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano MT512, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant TRA Hookless Tubeless ready Alloy Fr: 29", Rr: 27.5" 30mm inner width
HUBS	Giant TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 SRAM XD Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
SPOKES	Sapim Laser
TYRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	Tubeless prepared, 2.5" max tyre size, 36t max chainring size, MRP AMG CS chain guide

Price: \$6,299.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	77.5°	77.8°	78.2°	77.5°	77.8°	78.2°	76.5°	76.9°	77.2°	76.5°	76.9°	77.2°
Top Tube Length (mm)	558	557	556	589	588	587	622	621	621	654	653	653
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	62.7°	63.0°	63.4°	62.7°	63.0°	63.4°	62.7°	63.1°	63.4°	62.7°	63.1°	63.4°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	147	144	141	147	144	141	147	144	141	147	144	141
Wheelbase (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Chain Stay Length (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Bottom Bracket Drop (mm)	29	24	19	29	24	19	29	24	19	29	24	19
Stack (mm)	633	630	627	638	635	632	647	644	641	652	649	646
Reach (mm)	418	421	426	448	452	456	468	471	476	499	503	507
Stand Over Height (mm)	714	718	723	733	738	742	746	750	755	762	766	771
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.