

REIGN 1



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Blue Dragonfly/Black/Chrome
CUADRO	ALUXX SL-grade aluminum front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
HORQUILLA	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTIGUADOR	Fox Float X Performance Elite, 205/62.5, custom tuned for Giant
COMPONENTES	
MANILLAR	Giant Contact SL TR35, 800x35mm, 20mm rise
PUÑOS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
TIJA DE SILLÍN	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm
SILLÍN	Giant Romero
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano SLX SL-M7100, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	Shimano SLX RD-M7100
FRENOS	Shimano Deore BR-M6120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
PALANCAS DE FRENOS	Shimano Deore BL-M6100
CASETTE	Shimano SLX M7100, 10x51
CADENA	Shimano
JGO. PLATOS Y BIELAS	Shimano MT512, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
CAJA DE PEDALIER	Shimano, press fit

RUEDAS	
LLANTAS	Giant AM 29, alloy
BUJES	alloy, sealed
RADIOS	Stainless steel
CUBIERTAS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

Precio: 4.349,00 €

GEOMETRÍA

CUADRO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Longitud del tubo del sillín (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	257			383			308			333
Ángulo del tubo del sillín	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°
Longitud del tubo superior (mm) (mm)	556	555	555	587	586	585	620	620	619	652
Longitud del tubo de dirección (mm) (mm)	100			105			115			120
Ángulo del tubo de dirección	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°
Inclinación de la horquilla (mm)	44			44			44			44
Trail (mm) (mm)	140	138	135	140	138	135	140	138	135	140
Distancia entre ejes (mm) (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304
Longitud de la vaina (mm) (mm)	445	443	442	445	443	442	445	443	442	445
Caída del eje de pedalier (mm) (mm)	35	30	25	35	30	25	35	30	25	35
Stack (mm) (mm)	627	624	622	632	629	626	641	638	635	645
Reach (mm) (mm)	426	430	434	456	460	464	476	480	484	506
Altura del suelo al tubo (mm) (mm)	723	727	732	743	747	752	756	760	765	771
Ancho del manillar (mm) (mm)	800			800			800			800
Longitud de la potencia (mm) (mm)	40			40			40			40
Longitud de las bielas (mm) (mm)	165			170			170			170
Tamaño de ruedas	29"			29"			29"			29"

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.