



## ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Blue Dragonfly/Black/Chrome
CUADRO	ALUXX SL-grade aluminum front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
TIJERA	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTIGUADOR	Fox Float X Performance Elite, 205/62.5, custom tuned for Giant
COMPONENTES	
MANUBRIO	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
POSTE DE ASIENTO	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm
ASIENTO	Giant
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano SLX SL-M7100, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	Shimano SLX RD-M7100
FRENOS	Shimano Deore BR-M6120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
PALANCAS DE FRENOS	Shimano Deore BL-M6100
CASSETTE	Shimano SLX M7100, 10x51
CADENA	Shimano
MULTIPLICACIÓN	Shimano MT512, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant AM 29, alloy
MAZAS	alloy, sealed
RAYOS	Stainless steel
NEUMÁTICOS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

**Precio: \$89,990.00**

## GEOMETRÍA

CUADRO	S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longitud de la Base del Poste de Asiento (mm)	400			425			450		
Seat Post Insertion Depth (mm)	257			383			308		
Ángulo de la Base del Poste de Asiento	78.3°	78.7°	79.0°	78.3°	78.7°	79.0°	77.3°	77.7°	78.0°
Longitud del Tubo Superior (mm)	556	555	555	587	586	585	620	620	619
Longitud del Telescopio (mm)	100			105			115		
Ángulo del Telescopio	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°
Rake (mm)	44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135
Distancia entre Ejes (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269
Longitud de Vaina Inferior (mm)	445	443	442	445	443	442	445	443	442
Caída del Eje de Centro (mm)	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635
Reach (mm)	426	430	434	456	460	464	476	480	484
Altura del Tubo Superior al Suelo (mm)	723	727	732	743	747	752	756	760	765
Ancho del Manubrio (mm)	800			800			800		
Longitud de la Potencia (mm)	40			40			40		
Longitud de la Biela (mm)	165			170			170		
Tamaño de las Ruedas	29"			29"			29"		

Todas las especificaciones están sujetas a cambios sin previo aviso.