



TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Blue Dragonfly/Black/Chrome
CADRE	ALUXX SL-grade aluminum front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
FOURCHE	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTISSEUR	Fox Float X Performance Elite, 205/62.5, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact SL TR35, 800x35mm, 20mm rise
POIGNÉES	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
TIGE DE SELLE	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm
SELLE	Giant Romero
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	Shimano SLX SL-M7100, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano SLX RD-M7100
FREINS	Shimano Deore BR-M6120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
LEVIERS DE FREIN	Shimano Deore BL-M6100
CASSETTE	Shimano SLX M7100, 10x51
CHAÎNE	Shimano
PÉDALIER	Shimano MT512, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOITIER DE PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant AM 29, alloy
MOYEUX	alloy, sealed
RAYONS	Stainless steel
PNEUS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 4 350,00 €

GÉOMÉTRIE

CADRE	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longueur de tube de selle (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	257			383			308			333		
Angle de tube de selle	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°	77,7°	
Longueur du tube supérieur (mm)	556	555	555	587	586	585	620	620	619	652	652	
Longueur du tube de direction (mm)	100			105			115			120		
Angle du tube de direction	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	
Déport de fourche (mm)	44			44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135	140	138	
Empattement (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	
Longueur des bases (mm)	445	443	442	445	443	442	445	443	442	445	443	
Drop du boîtier de pédalier (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	
Hauteur en statique (mm)	723	727	732	743	747	752	756	760	765	771	777	
Largeur de cintre (mm)	800			800			800			800		
Longueur de potence (mm)	40			40			40			40		
Longueur des manivelles (mm)	165			170			170			170		
Diamètre des roues	29"			29"			29"			29"		

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.