



## SPECS

CADRU	
MARIMI	S, M, L, XL
CULORI	Blue Dragonfly/Black/Chrome
CADRU	ALUXX SL-grade aluminum front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
FURCA	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
SOC	Fox Float X Performance Elite, 205/62.5, custom tuned for Giant
COMPONENTE	
GHIDON	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
PIPA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
TIJA SA	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm
SA	Giant Romero
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano SLX SL-M7100, 1x12
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	Shimano SLX RD-M7100
FRANE	Shimano Deore BR-M6120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
MANETE FRANA	Shimano Deore BL-M6100
PINIOANE	Shimano SLX M7100, 10x51
LANT	Shimano
ANGRENAJ	Shimano MT512, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

## ROTI

JANTE	Giant AM 29, alloy
BUTUCI	alloy, sealed
SPITE	Stainless steel
ANVELOPE	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

## GEOMETRIE

CADRU	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	257			383			308			333		
Seat Tube Angle	78,3°   78,7°   79,0°			78,3°   78,7°   79,0°			77,3°   77,7°   78,0°			77,3°   77,7°   78,0°		
Top Tube Length (mm)	556	555	555	587	586	585	620	620	619	652	652	651
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	63,5°   63,9°   64,2°			63,5°   63,9°   64,2°			63,5°   63,9°   64,2°			63,5°   63,9°   64,2°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Wheelbase (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Chain Stay Length (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Bottom Bracket Drop (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	639
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Stand Over Height (mm)	723	727	732	743	747	752	756	760	765	771	777	782
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29"			29"			29"			29"		

Toate specificatiile enumerate se pot schimba fara notificare prealabila.