



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	S, M, L, XL
FARBY	Blue Dragonfly/Black/Chrome
RÁM	ALUXX SL-grade aluminum front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
VIDLICA	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
TLMIČ	Fox Float X Performance Elite, 205/62.5, custom tuned for Giant
KOMPONENTY	
RIADIDLÁ	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPY	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
PREDSTAVEC	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEDLOVKA	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm
SEDADLO	Giant Romero
PEDÁLE	N/A
POHON	
RADENIE	Shimano SLX SL-M7100, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	Shimano SLX RD-M7100
BRZDY	Shimano Deore BR-M6120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BRZDOVÉ PÁKY	Shimano Deore BL-M6100
KAZETA	Shimano SLX M7100, 10x51
REŤAZ	Shimano
KLUKY	Shimano MT512, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
STREDOVÉ ZLOŽENIE	Shimano, press fit

KOLESÁ	
RÁFIKY	Giant AM 29, alloy
NÁBOJE	alloy, sealed
ŠPICE	Stainless steel
PNEUMATIKY	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
DOPLNKY	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

Cena: 4 349 €

GEOMETRIA

RÁM	S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	400			425			450		
Hĺbka vloženia sedlovky (mm)	257			383			308		
Uhol sedlovej trubky	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°
Dĺžka hornej rámovej trubky (mm)	556	555	555	587	586	585	620	620	619
Dĺžka hlavovej trubky (mm)	100			105			115		
Uhol hlavovej trubky	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°
Offset vidlice (mm)	44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135
Rázvor (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269
Dĺžka zadnej stavby (mm)	445	443	442	445	443	442	445	443	442
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	35	30	25	35	30	25	35	30	25
Stack - výška riadenia (mm)	627	624	622	632	629	626	641	638	635
Reach (mm)	426	430	434	456	460	464	476	480	484
Výška rámu od zeme (mm)	723	727	732	743	747	752	756	760	765
Šírka riaditok (mm)	800			800			800		
Dĺžka predstavca (mm)	40			40			40		
Dĺžka kľúk (mm)	165			170			170		
Rozmer kolies	29"			29"			29"		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.