



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Blue Dragonfly/Black/Chrome
OKVIR	ALUXX SL-grade aluminum front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
VILICE	Fox 38 Performance Elite, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTIZER	Fox Float X Performance Elite, 205/62.5, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm
SEDEŽ	Giant Romero
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano SLX SL-M7100, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano SLX RD-M7100
ZAVORE	Shimano Deore BR-M6120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
ZAVORNE ROČICE	Shimano Deore BL-M6100
VERIŽNIK	Shimano SLX M7100, 10x51
VERIGA	Shimano
GONILKE Z VERIŽNIKI	Shimano MT512, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

## OBROČNIKI

OBROČI	Giant AM 29, alloy
PESTA	alloy, sealed
NAPERE	Stainless steel
PLAŠČI	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

## GEOMETRIJA

OKVIR	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Dolžina sedežne cevi (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	257			383			308			333
Kot sedežne cevi	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°
Top Tube Length (mm)	556	555	555	587	586	585	620	620	619	652
Višina glave okvirja (mm)	100			105			115			120
Krmlini kot	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°
Zamik vpetja osi (mm)	44			44			44			44
Trail (mm)	140	138	135	140	138	135	140	138	135	140
Medosna razdalja (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1300
Dolžina cevi ob verigi (mm)	445	443	442	445	443	442	445	443	442	445
Bottom Bracket Drop (mm)	35	30	25	35	30	25	35	30	25	35
Oddaljenost zgornje cevi od gonilne osi (mm)	627	624	622	632	629	626	641	638	635	645
Doseg (mm)	426	430	434	456	460	464	476	480	484	506
Višina zgornje cevi (mm)	723	727	732	743	747	752	756	760	765	777
Širina krmila (mm)	800			800			800			800
Dolžina opore krmila (mm)	40			40			40			40
Dolžina gonilke (mm)	165			170			170			170
Velikost obročnikov	29"			29"			29"			29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.