

REIGN 2



SPECS

QUADRO	
TAMANHOS	S, M, L, XL
CORES	Black/Pyrite Brown
QUADRO	ALUXX SL-grade aluminum front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
FORQUILHA	Fox 38 Rhythm, 170mm, GRIP damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTECEDORES	Fox Float Performance, 205/62.5, custom tuned for Giant
COMPONENTES	
GUIADOR	Giant Contact TR35, 800x35mm, 20mm rise
PUNHOS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
AVANÇO	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
ESPIGÃO DE SELIM	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm
SELIM	Giant Romero
PEDAIS	N/A
TRANSMISSÃO	
MANETES	Shimano Deore SL-M6100, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	Shimano SLX RD-M7100
TRAVÕES	Shimano Deore BR-MT520, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
MANÍPULOS DOS TRAVÕES	Shimano Deore BL-MT501
CASSETTE	Shimano Deore M6100, 10x51
CORRENTE	KMC X12
CONJUNTO PEDALEIRO	Praxis Cadet HD M24, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRAL	Praxis, press fit

RODAS	
AROS	Giant AM 29, alloy
CUBOS	alloy, sealed
RAIOS	Stainless steel
PNEUS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

Preço: 3 149,00 €

GEOMETRIA

QUADRO	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Comprimento do tubo do assento (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	257			383			308			333		
Ângulo do tubo do assento	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°	77,7°	78,0°
Comprimento do tubo superior (mm)	556	555	555	587	586	585	620	620	619	652	652	651
Comprimento do tubo principal (mm)	100			105			115			120		
Ângulo do tubo principal	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°
Garfo ancinho (mm)	44			44			44			44		
Trilha (mm)	140	138	135	140	138	135	140	138	135	140	138	135
distância entre eixos (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Comprimento Chain Stay (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Suporte inferior (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Pilha (mm)	627	624	622	632	629	626	641	638	635	645	642	639
Alcançar (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Altura do standover (mm)	723	727	732	743	747	752	756	760	765	771	775	780
Largura do guidão (mm)	800			800			800			800		
Comprimento da haste (mm)	40			40			40			40		
Comprimento da Manivela (mm)	165			170			170			170		
Tamanho da roda	29"			29"			29"			29"		

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.