



SPECS

| CADRU | |
|-----------------------------------|--|
| MARIMI | S, M, L, XL |
| CULORI | Black/Pyrite Brown |
| CADRU | ALUXX SL-grade aluminum front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage |
| FURCA | Fox 38 Rhythm, 170mm, GRIP damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant |
| SOC | Fox Float Performance, 205/62.5, custom tuned for Giant |
| COMPONENTE | |
| GHIDON | Giant Contact TR35, 800x35mm, 20mm rise |
| GRIPS | Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm |
| PIPA | Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm |
| TIJA SA | Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm |
| SA | Giant Romero |
| PEDALE | N/A |
| SISTEMUL DE SCHIMBARE A VITEZELOR | |
| MANETE SCHIMBATOR | Shimano Deore SL-M6100, 1x12 |
| SCHIMBATOR FATA | N/A |
| SCHIMBATOR SPATE | Shimano SLX RD-M7100 |
| FRANE | Shimano Deore BR-MT520, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm |
| MANETE FRANA | Shimano Deore BL-MT501 |
| PINIOANE | Shimano Deore M6100, 10x51 |
| LANT | KMC X12 |
| ANGRENAJ | Praxis Cadet HD M24, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm |
| BOTTOM BRACKET | Praxis, press fit |

| ROTI | |
|----------|--|
| JANTE | Giant AM 29, alloy |
| BUTUCI | alloy, sealed |
| SPITE | Stainless steel |
| ANVELOPE | [F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless |
| EXTRAS | tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide |

GEOMETRIE

| CADRU | S | | | M | | | L | | | XL | | |
|--------------------------------|-----------------------|------|------|-----------------------|------|------|-----------------------|------|------|-----------------------|------|------|
| | LOW | MID | HIGH | LOW | MID | HIGH | LOW | MID | HIGH | LOW | MID | HIGH |
| Seat Tube Length (mm) | 400 | | | 425 | | | 450 | | | 475 | | |
| Seat Post Insertion Depth (mm) | 257 | | | 383 | | | 308 | | | 333 | | |
| Seat Tube Angle | 78,3° 78,7° 79,0° | | | 78,3° 78,7° 79,0° | | | 77,3° 77,7° 78,0° | | | 77,3° 77,7° 78,0° | | |
| Top Tube Length (mm) | 556 | 555 | 555 | 587 | 586 | 585 | 620 | 620 | 619 | 652 | 652 | 651 |
| Head Tube Length (mm) | 100 | | | 105 | | | 115 | | | 120 | | |
| Head Tube Angle | 63,5° 63,9° 64,2° | | | 63,5° 63,9° 64,2° | | | 63,5° 63,9° 64,2° | | | 63,5° 63,9° 64,2° | | |
| Fork Rake (mm) | 44 | | | 44 | | | 44 | | | 44 | | |
| Trail (mm) | 140 | 138 | 135 | 140 | 138 | 135 | 140 | 138 | 135 | 140 | 138 | 135 |
| Wheelbase (mm) | 1214 | 1213 | 1212 | 1246 | 1245 | 1244 | 1271 | 1270 | 1269 | 1304 | 1303 | 1302 |
| Chain Stay Length (mm) | 445 | 443 | 442 | 445 | 443 | 442 | 445 | 443 | 442 | 445 | 443 | 442 |
| Bottom Bracket Drop (mm) | 35 | 30 | 25 | 35 | 30 | 25 | 35 | 30 | 25 | 35 | 30 | 25 |
| Stack (mm) | 627 | 624 | 622 | 632 | 629 | 626 | 641 | 638 | 635 | 645 | 642 | 639 |
| Reach (mm) | 426 | 430 | 434 | 456 | 460 | 464 | 476 | 480 | 484 | 506 | 510 | 514 |
| Stand Over Height (mm) | 723 | 727 | 732 | 743 | 747 | 752 | 756 | 760 | 765 | 771 | 777 | 782 |
| Handlebar Width (mm) | 800 | | | 800 | | | 800 | | | 800 | | |
| Stem Length (mm) | 40 | | | 40 | | | 40 | | | 40 | | |
| Crank Length (mm) | 165 | | | 170 | | | 170 | | | 170 | | |
| Wheel Size | 29" | | | 29" | | | 29" | | | 29" | | |

Toate specificatiile enumerate se pot schimba fara notificare prealabila.