



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	S, M, L, XL
ЦВЯТ	Digital Blurple/Raw Carbon
РАМКА	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
ВИЛКА	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
ЗАДЕН АМОРТИСЬОР	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
ГРИПОВЕ	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
ЛАПА	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
КОЛЧЕ ЗА СЕДАЛКА	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
СЕДАЛКА	Giant Romero SL
ПЕДАЛИ	platform
DRIVETRAIN	
КОМАНДИ	SRAM AXS Pod, discrete clamp, 1x12
ПРЕДЕН ДЕРАЙЛЪОР	N/A
ЗАДЕН ДЕРАЙЛЪОР	SRAM GX Eagle Transmission
СПИРАЧКИ	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano SLX BL-M7100
КАСЕТА	SRAM GX Eagle Transmission, 10x52
ВЕРИГА	SRAM GX Eagle Transmission
КУРБЕЛ	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
ГЛАВИНИ	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
СПИЦИ	Stainless steel
ГУМИ	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
ЕКСТРИ	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

ГЕОМЕТРИЯ

PAMKA	S			M			L			XL		
	LOW MID HIGH			LOW MID HIGH			LOW MID HIGH			LOW MID HIGH		
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	78,3° 78,7° 79,0°			78,3° 78,7° 79,0°			77,3° 77,7° 78,0°			77,3° 77,7° 78,0°		
Top Tube Length (mm)	556	555	555	587	586	585	620	620	619	652	652	652
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	63,5° 63,9° 64,2°			63,5° 63,9° 64,2°			63,5° 63,9° 64,2°			63,5° 63,9° 64,2°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Wheelbase (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Chain Stay Length (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Bottom Bracket Drop (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	639
Обсер (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Stand Over Height (mm)	720	724	729	735	739	744	751	756	760	746	751	756
Ширина на Кормило (mm)	800			800			800			800		
Дължина на Лапа (mm)	40			40			40			40		
Дължина на Курбел (mm)	165			170			170			170		
Размер на Каплите	29"			29"			29"			29"		

All specifications listed are subject to change without notice.