



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	S, M, L, XL
ЦВЯТ	Mercury/Raw Carbon
РАМКА	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
ВИЛКА	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
ЗАДЕН АМОРТИСЬОР	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact TR35, 800x35mm, 35mm rise
ГРИПОВЕ	Giant Tactal Pro Single
ЛАПА	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
КОЛЧЕ ЗА СЕДАЛКА	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
СЕДАЛКА	Giant Romero SL
DRIVETRAIN	
КОМАНДИ	SRAM AXS Pod, discrete clamp, 1x12
ПРЕДЕН ДЕРАЙЛЪОР	N/A
ЗАДЕН ДЕРАЙЛЪОР	SRAM GX Eagle Transmission
СПИРАЧКИ	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	TRP DH-R EVO, hydraulic
КАСЕТА	SRAM GX Eagle Transmission, 10x52
ВЕРИГА	SRAM GX Eagle Transmission
КУРБЕЛ	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
ГЛАВИНИ	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
СПИЦИ	Sapim, 28, straight pull, DBL Technology
ГУМИ	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
ЕКСТРИ	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

ГЕОМЕТРИЯ

РАМКА	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°	76,5°	76,9°	77,2°	76,5°	76,9°	77,2°
Top Tube Length (mm)	558	557	556	589	588	587	622	621	621	654	653	653
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°	62,7°	63,1°	63,4°	62,7°	63,1°	63,4°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	147	144	141	147	144	141	147	144	141	147	144	141
Wheelbase (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1303
Chain Stay Length (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Bottom Bracket Drop (mm)	29	24	19	29	24	19	29	24	19	29	24	19
Stack (mm)	633	630	627	638	635	632	647	644	641	652	649	646
Обсер (mm)	418	421	426	448	452	456	468	471	476	499	503	507
Stand Over Height (mm)	714	718	723	733	738	742	746	750	755	762	766	771
Ширина на Кормило (mm)	800			800			800			800		
Дължина на Лапа (mm)	40			40			40			40		
Дължина на Курбел (mm)	165			170			170			170		
Размер на Каплите	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

All specifications listed are subject to change without notice.