

REIGN ADVANCED 1

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Mercury/Raw Carbon
FRAME	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
FORK	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SADDLE	Giant Romero SL
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle Transmission
BRAKES	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
BRAKE LEVERS	TRP DH-R EVO, hydraulic
CASSETTE	SRAM GX Eagle Transmission, 10x52
CHAIN	SRAM GX Eagle Transmission
CRANKSET	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
HUBS	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400	425	450	475								
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	77,5° 77,8°	78,2°	77,5° 77,8°	78,2°	76,5° 76,9°	77,2°	76,5° 76,9°	77,2°	76,5° 76,9°	77,2°	76,5° 76,9°	77,2°
Top Tube Length (mm)	558 557 556	589 588 587	622 621 621	654 653 653								
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	62,7° 63,0° 63,4°	62,7° 63,0° 63,4°	62,7° 63,1° 63,4°	62,7° 63,1° 63,4°	62,7° 63,1° 63,4°	62,7° 63,1° 63,4°	62,7° 63,1° 63,4°	62,7° 63,1° 63,4°	62,7° 63,1° 63,4°	62,7° 63,1° 63,4°	62,7° 63,1° 63,4°	62,7° 63,1° 63,4°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	147 144 141	147 144 141	147 144 141	147 144 141	147 144 141	147 144 141	147 144 141	147 144 141	147 144 141	147 144 141	147 144 141	147 144 141
Wheelbase (mm)	1214 1213 1212	1246 1245 1244	1271 1270 1269	1304 1303 1303	1330 1329 1328	1355 1354 1353	1380 1379 1378	1405 1404 1403	1430 1429 1428	1455 1454 1453	1480 1479 1478	1505 1504 1503
Chain Stay Length (mm)	445 443 442	445 443 442	445 443 442	445 443 442	445 443 442	445 443 442	445 443 442	445 443 442	445 443 442	445 443 442	445 443 442	445 443 442
Bottom Bracket Drop (mm)	29 24 19	29 24 19	29 24 19	29 24 19	29 24 19	29 24 19	29 24 19	29 24 19	29 24 19	29 24 19	29 24 19	29 24 19
Stack (mm)	633 630 627	638 635 632	647 644 641	652 649 646	657 654 651	666 663 660	675 672 669	684 681 678	693 690 687	702 699 696	711 708 705	720 717 714
Reach (mm)	418 421 426	448 452 456	468 471 476	499 503 507	529 533 537	559 563 567	589 593 597	619 623 627	649 653 657	679 683 687	709 713 717	739 743 747
Stand Over Height (mm)	714 718 723	733 738 742	746 750 755	762 766 771	778 782 787	794 798 803	810 814 819	826 830 835	842 846 851	858 862 867	874 878 883	890 894 899
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

All specifications listed are subject to change without notice.