



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	S, M, L, XL
ΧΡΩΜΑΤΑ	Digital Blurple/Raw Carbon
ΣΚΕΛΕΤΟΣ	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
ΠΙΡΟΥΝΙ	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
ΑΝΑΡΤΗΣΗ	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
ΛΑΙΜΟΣ ΣΕΛΛΑΣ	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
ΣΕΛΛΑ	Giant Romero SL
ΠΕΝΤΑΛ	platform
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	SRAM AXS Pod, discrete clamp, 1x12
ΝΤΕΡΑΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	N/A
ΝΤΕΡΑΓΙΕΡ ΟΠΙΣΘΙΟ.	SRAM GX Eagle Transmission
ΦΡΕΝΑ	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
ΜΑΝΕΤΤΕΣ ΦΡΕΝΩΝ	Shimano SLX BL-M7100
CASETTE Η ΕΛΕΥΘΕΡΟ	SRAM GX Eagle Transmission, 10x52
ΑΛΥΣΙΔΑ	SRAM GX Eagle Transmission
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
ΚΕΝΤΡΑ	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
ΑΚΤΙΝΕΣ	Stainless steel
ΕΛΑΣΤΙΚΑ	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°	77,7°	78,0°
Top Tube Length (mm)	556	555	555	587	586	585	620	620	619	652	652	651
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Wheelbase (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Chain Stay Length (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Bottom Bracket Drop (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	639
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Stand Over Height (mm)	720	724	729	735	739	744	751	756	760	746	751	756
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29"			29"			29"			29"		

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση