



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	S, M, L, XL
ΧΡΩΜΑΤΑ	Mercury/Raw Carbon
ΣΚΕΛΕΤΟΣ	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
ΠΙΡΟΥΝΙ	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
ΑΝΑΡΤΗΣΗ	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
ΛΑΙΜΟΣ ΣΈΛΛΑΣ	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
ΣΈΛΛΑ	Giant Romero SL
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	SRAM AXS Pod, discrete clamp, 1x12
ΝΤΕΡΑΓΊΕΡ ΕΜΠΡΟΣΘΙΟ	N/A
ΝΤΕΡΑΓΊΕΡ ΟΠΙΣΘΙΟ	SRAM GX Eagle Transmission
ΦΡΈΝΑ	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
ΜΑΝΈΤΤΕΣ ΦΡΈΝΩΝ	TRP DH-R EVO, hydraulic
CASETTE Ή ΕΛΕΥΘΕΡΟ	SRAM GX Eagle Transmission, 10x52
ΑΛΥΣΊΔΑ	SRAM GX Eagle Transmission
ΔΙΣΚΟΒΡΑΧΊΩΝΑΣ	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
ΚΕΝΤΡΑ	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
ΑΚΤΙΝΕΣ	Sapim, 28, straight pull, DBL Technology
ΕΛΑΣΤΙΚΑ	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°	76,5°	76,9°	77,2°	76,5°	76,9°	77,2°
Top Tube Length (mm)	558	557	556	589	588	587	622	621	621	654	653	653
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°	62,7°	63,1°	63,4°	62,7°	63,1°	63,4°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	147	144	141	147	144	141	147	144	141	147	144	141
Wheelbase (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1303
Chain Stay Length (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Bottom Bracket Drop (mm)	29	24	19	29	24	19	29	24	19	29	24	19
Stack (mm)	633	630	627	638	635	632	647	644	641	652	649	646
Reach (mm)	418	421	426	448	452	456	468	471	476	499	503	507
Stand Over Height (mm)	714	718	723	733	738	742	746	750	755	762	766	771
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση