

REIGN ADVANCED 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Digital Blurple/Raw Carbon
FRAME	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip 3 position, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, integrated downtube storage, 55mm Chainline
FORK	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
SHOCK	Fox Float X2 Factory, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 35mm
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle T-Type AXS
BRAKES	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]203mm
BRAKE LEVERS	Shimano SLX BL-M7100
CASSETTE	SRAM GX, T-Type 10x52
CHAIN	SRAM GX T-Type
CRANKSET	SRAM GX T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	Tubeless prepared, 2.5" max tyre size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Price: \$9,999.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	78.3° 78.7° 79.0°	78.3° 78.7° 79.0°	77.3° 77.7° 78.0°	77.3° 77.7° 78.0°	77.3° 77.7° 78.0°	77.3° 77.7° 78.0°	77.3° 77.7° 78.0°	77.3° 77.7° 78.0°	77.3° 77.7° 78.0°	77.3° 77.7° 78.0°	77.3° 77.7° 78.0°	77.3° 77.7° 78.0°
Top Tube Length (mm)	556 555 555	587 586 585	620 620 619	652 652 651								
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°	63.5° 63.9° 64.2°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	140 138 135	140 138 135	140 138 135	140 138 135			140 138 135			140 138 135		
Wheelbase (mm)	1214 1213 1212	1246 1245 1244	1271 1270 1269	1304 1303 1302			1330 1329 1328			1355 1354 1353		
Chain Stay Length (mm)	445 443 442	445 443 442	445 443 442	445 443 442			445 443 442			445 443 442		
Bottom Bracket Drop (mm)	35 30 25	35 30 25	35 30 25	35 30 25			35 30 25			35 30 25		
Stack (mm)	627 624 622	632 629 626	641 638 635	645 642 639			650 647 644			655 652 649		
Reach (mm)	426 430 434	456 460 464	476 480 484	506 510 514			526 530 534			546 550 554		
Stand Over Height (mm)	720 724 729	735 739 744	751 756 760	746 751 756			761 766 770			776 781 786		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29"			29"			29"			29"		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.