



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Mercury/Raw Carbon
FRAME	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
FORK	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SADDLE	Giant Romero SL
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle Transmission
BRAKES	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
BRAKE LEVERS	TRP DH-R EVO, hydraulic
CASSETTE	SRAM GX Eagle Transmission, 10x52
CHAIN	SRAM GX Eagle Transmission
CRANKSET	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
HUBS	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Price: ₹ 7,399.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	77.5° 77.8° 78.2°			77.5° 77.8° 78.2°			76.5° 76.9° 77.2°			76.5° 76.9° 77.2°		
Top Tube Length (mm)	558 557 556			589 588 587			622 621 621			654 653 653		
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	62.7° 63.0° 63.4°			62.7° 63.0° 63.4°			62.7° 63.1° 63.4°			62.7° 63.1° 63.4°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	147 144 141			147 144 141			147 144 141			147 144 141		
Wheelbase (mm)	1214 1213 1212			1246 1245 1244			1271 1270 1269			1304 1303 1302		
Chain Stay Length (mm)	445 443 442			445 443 442			445 443 442			445 443 442		
Bottom Bracket Drop (mm)	29 24 19			29 24 19			29 24 19			29 24 19		
Stack (mm)	633 630 627			638 635 632			647 644 641			652 649 646		
Reach (mm)	418 421 426			448 452 456			468 471 476			499 503 507		
Stand Over Height (mm)	714 718 723			733 738 742			746 750 755			762 766 771		
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.