



SPECIFIKACIJE

OKVIR	
VELIČINE	S, M, L, XL
BOJE	Digital Blurple/Raw Carbon
OKVIR	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
VILICA	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTIZER	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
KOMPONENTE	
VOLAN	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
LULA VOLANA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
CIJEV SJEDALA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SJEDALO	Giant Romero SL
PEDALE	platform
POGON	
RUČICE MJENJAČA	SRAM AXS Pod, discrete clamp, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM GX Eagle Transmission
KOČNICE	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
RUČICE KOČNICA	Shimano SLX BL-M7100
KAZETA	SRAM GX Eagle Transmission, 10x52
LANAC	SRAM GX Eagle Transmission
POGON	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
ŽBICE	Stainless steel
GUME	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
DODACI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRIJA

OKVIR	S			M		
	LOW	MID	HIGH	LOW	MID	HIGH
Dužina cijevi sjedala (mm)	400			425		
Seat Post Insertion Depth (mm)	262			287		
Kut cijevi sjedala	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°
Dužina gornje cijevi (mm)	556	555	555	587	586	585
Dužina prednje cijevi (mm)	100			105		
Kut vilice	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°
Zakrivljenost vilice (offset) (mm)	44			44		
Staza (mm)	140	138	135	140	138	135
Međuosovinski razmak kotača (mm)	1214	1213	1212	1246	1245	1244
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	445	443	442	445	443	442
Položaj osovine pogona (mm)	35	30	25	35	30	25
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	627	624	622	632	629	626
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	426	430	434	456	460	464
Prekoračna visina (mm)	720	724	729	735	739	744
Širina volana (mm)	800			800		
Dužina lule volana (mm)	40			40		
Dužina poluge pedale (mm)	165			170		
Veličina kotača	29"			29"		

Sve navedene specifikacije podložne su promjeni bez prethodne najave.