



## SPECIFIKACIJE

OKVIR	
VELIČINE	S, M, L, XL
BOJE	Mercury/Raw Carbon
OKVIR	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
VILICA	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
AMORTIZER	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
KOMPONENTE	
VOLAN	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
LULA VOLANA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
CIJEV SJEDALA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SJEDALO	Giant Romero SL
POGON	
RUČICE MJENJAČA	SRAM AXS Pod, discrete clamp, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM GX Eagle Transmission
KOČNICE	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
RUČICE KOČNICA	TRP DH-R EVO, hydraulic
KAZETA	SRAM GX Eagle Transmission, 10x52
LANAC	SRAM GX Eagle Transmission
POGON	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NABE	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
ŽBICE	Sapim, 28, straight pull, DBL Technology
GUME	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
DODACI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

## GEOMETRIJA

OKVIR	S			M		
	LOW	MID	HIGH	LOW	MID	HIGH
Dužina cijevi sjedala (mm)	400			425		
Seat Post Insertion Depth (mm)	262			287		
Kut cijevi sjedala	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°
Dužina gornje cijevi (mm)	558	557	556	589	588	587
Dužina prednje cijevi (mm)	100			105		
Kut vilice	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°
Zakrivljenost vilice (offset) (mm)	44			44		
Staza (mm)	147	144	141	147	144	141
Međuosovinski razmak kotača (mm)	1214	1213	1212	1246	1245	1244
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	445	443	442	445	443	442
Položaj osovine pogona (mm)	29	24	19	29	24	19
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	633	630	627	638	635	632
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	418	421	426	448	452	456
Prekoračna visina (mm)	714	718	723	733	738	742
Širina volana (mm)	800			800		
Dužina lule volana (mm)	40			40		
Dužina poluge pedale (mm)	165			170		
Veličina kotača	29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Sve navedene specifikacije podložne su promjeni bez prethodne najave.