



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Digital Blurple/Raw Carbon
FRAME	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
FORK	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
SHOCK	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SADDLE	Giant Romero SL
PEDALS	platform
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle Transmission
BRAKES	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BRAKE LEVERS	Shimano SLX BL-M7100
CASSETTE	SRAM GX Eagle Transmission, 10x52
CHAIN	SRAM GX Eagle Transmission
CRANKSET	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
SPOKES	Stainless steel
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	78,3° 78,7° 79,0°			78,3° 78,7° 79,0°			77,3° 77,7° 78,0°			77,3° 77,7° 78,0°		
Top Tube Length (mm)	556	555	555	587	586	585	620	620	619	652	652	651
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	63,5° 63,9° 64,2°			63,5° 63,9° 64,2°			63,5° 63,9° 64,2°			63,5° 63,9° 64,2°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Wheelbase (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Chain Stay Length (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Bottom Bracket Drop (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	639
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Stand Over Height (mm)	720	724	729	735	739	744	751	756	760	746	751	756
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29"			29"			29"			29"		

All specifications listed are subject to change without notice.