REIGN ADVANCED 1

SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Mercury/Raw Carbon
FRAME	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
FORK	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SADDLE	Giant Romero SL
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle Transmission
BRAKES	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
BRAKE LEVERS	TRP DH-R EVO, hydraulic
CASSETTE	SRAM GX Eagle Transmission, 10x52
CHAIN	SRAM GX Eagle Transmission
CRANKSET	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
HUBS	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRY

FRAME	S	M	L	XL
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIG
Seat Tube Length (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	262	287	312	337
Seat Tube Angle	77,5° | 77,8° | 78,2°	77,5° | 77,8° | 78,2°	76,5° | 76,9° | 77,2°	76,5° | 76,9° | 7
Top Tube Length (mm)	558 | 557 | 556	589 | 588 | 587	622 | 621 | 621	654 | 653 | 653
Head Tube Length (mm)	100	105	115	120
Head Tube Angle	62,7° | 63,0° | 63,4°	62,7° | 63,0° | 63,4°	62,7° | 63,1° | 63,4°	62,7° | 63,1° | 6
Fork Rake (mm)	44	44	44	44
Trail (mm)	147 | 144 | 141	147 | 144 | 141	147 | 144 | 141	147 | 144 | 141
Wheelbase (mm)	1214 | 1213 | 1212	1246 | 1245 | 1244	1271 | 1270 | 1269	1304 | 1303 | 13
Chain Stay Length (mm)	445 | 443 | 442	445 | 443 | 442	445 | 443 | 442	445 | 443 | 442
Bottom Bracket Drop (mm)	29 | 24 | 19	29 | 24 | 19	29 | 24 | 19	29 | 24 | 19
Stack (mm)	633 | 630 | 627	638 | 635 | 632	647 | 644 | 641	652 | 649 | 646
Reach (mm)	418 | 421 | 426	448 | 452 | 456	468 | 471 | 476	499 | 503 | 507
Stand Over Height (mm)	714 | 718 | 723	733 | 738 | 742	746 | 750 | 755	762 | 766 | 771
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	40	40	40	40
Crank Length (mm)	165	170	170	170
Wheel Size	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]

All specifications listed are subject to change without notice.