

# REIGN ADVANCED 1

**GIANT**

## SPECS

TELAIO	
<b>TAGLIE</b>	S, M, L, XL
<b>COLORAZIONI</b>	Digital Blurple/Raw Carbon
<b>TELAIO</b>	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
<b>FORCELLA</b>	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
<b>AMMORTIZZATORE</b>	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
COMPONENTISTICA	
<b>MANUBRIO</b>	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
<b>MANOPOLE</b>	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
<b>ATTACCO MANUBRIO</b>	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
<b>REGGISSELLA</b>	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
<b>SELLA</b>	Giant Romero SL
<b>PEDALI</b>	platform
SISTEMA DI TRASMISSIONE	
<b>CAMBIO</b>	SRAM AXS Pod, discrete clamp, 1x12
<b>DERAGLIATORE ANTERIORE</b>	N/A
<b>DERAGLIATORE POSTERIORE</b>	SRAM GX Eagle Transmission
<b>FRENI</b>	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
<b>COMANDI FRENO</b>	Shimano SLX BL-M7100
<b>PACCO PIGNONI</b>	SRAM GX Eagle Transmission, 10x52
<b>CATENA</b>	SRAM GX Eagle Transmission
<b>GUARNITURA</b>	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
<b>MOVIMENTO CENTRALE</b>	SRAM DUB, press fit

RUOTE	
<b>CERCHI</b>	Giant TRX 2.29 Carbon WheelSystem, 30mm inner width
<b>MOZZI</b>	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
<b>RAGGI</b>	Stainless steel
<b>COPERTONI</b>	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
<b>EXTRA</b>	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Prezzo: € 7.199

## GEOMETRIA

TELAIO	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Lunghezza Tubo Sella (mm)	400			425			450			475		
Profondità inserimento reggisella (mm)	262			287			312			337		
Angolo Tubo Sella	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°	77,7°	78,0°
Lunghezza Tubo Orizzontale (mm)	556	555	555	587	586	585	620	620	619	652	652	652
Lunghezza Tubo Sterzo (mm)	100			105			115			120		
Angolo Sterzo	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°
Rake Forcella (mm)	44			44			44			44		
Avancorsa (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Interasse (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Lunghezza Carro Posteriore (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Drop Movimento Centrale (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	640
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Altezza stand over (mm)	720	724	729	735	739	744	751	756	760	746	750	754
Larghezza Manubrio c/c (mm)	800			800			800			800		
Lunghezza Attacco Manubrio (mm)	40			40			40			40		
Lunghezza Pedivella (mm)	165			170			170			170		
Dimensione Ruote	29"			29"			29"			29"		

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.