

REIGN ADVANCED 1

GIANT



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Mercury/Raw Carbon
TELAIO	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
FORCELLA	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
AMMORTIZZATORE	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
COMPONENTISTICA	
MANUBRIO	Giant Contact TR35, 800x35mm, 35mm rise
MANOPOLE	Giant Tactal Pro Single
ATTACCO MANUBRIO	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
REGGISSELLA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SELLA	Giant Romero SL
SISTEMA DI TRASMISSIONE	
CAMBIO	SRAM AXS Pod, discrete clamp, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	SRAM GX Eagle Transmission
FRENI	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
COMANDI FRENO	TRP DH-R EVO, hydraulic
PACCO PIGNONI	SRAM GX Eagle Transmission, 10x52
CATENA	SRAM GX Eagle Transmission
GUARNITURA	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRALE	SRAM DUB, press fit

RUOTE	
CERCHI	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
MOZZI	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
RAGGI	Sapim, 28, straight pull, DBL Technology
COPERTONI	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRA	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Prezzo: € 7.199

GEOMETRIA

TELAIO	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Lunghezza Tubo Sella (mm)	400			425			450			475		
Profondità inserimento reggisella (mm)	262			287			312			337		
Angolo Tubo Sella	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°	76,5°	76,9°	77,2°	76,5°	76,9°	77,2°
Lunghezza Tubo Orizzontale (mm)	558	557	556	589	588	587	622	621	621	654	653	652
Lunghezza Tubo Sterzo (mm)	100			105			115			120		
Angolo Sterzo	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°	62,7°	63,1°	63,4°	62,7°	63,1°	63,4°
Rake Forcella (mm)	44			44			44			44		
Avancorsa (mm)	147	144	141	147	144	141	147	144	141	147	144	141
Interasse (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Lunghezza Carro Posteriore (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Drop Movimento Centrale (mm)	29	24	19	29	24	19	29	24	19	29	24	19
Stack (mm)	633	630	627	638	635	632	647	644	641	652	649	646
Reach (mm)	418	421	426	448	452	456	468	471	476	499	502	506
Altezza stand over (mm)	714	718	723	733	738	742	746	750	755	762	766	770
Larghezza Manubrio c/c (mm)	800			800			800			800		
Lunghezza Attacco Manubrio (mm)	40			40			40			40		
Lunghezza Pedivella (mm)	165			170			170			170		
Dimensione Ruote	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.