

# REIGN ADVANCED 1

**GIANT**



## SPECS

QUADRO	
TAMANHOS	S, M, L, XL
CORES	Mercury/Raw Carbon
QUADRO	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
FORQUILHA	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
AMORTECEDORES	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
COMPONENTES	
GUIADOR	Giant Contact TR35, 800x35mm, 35mm rise
PUNHOS	Giant Tactal Pro Single
AVANÇO	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
ESPIGÃO DE SELIM	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SELIM	Giant Romero SL
TRANSMISSÃO	
MANETES	SRAM AXS Pod, discrete clamp, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	SRAM GX Eagle Transmission
TRAVÕES	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
MANÍPULOS DOS TRAVÕES	TRP DH-R EVO, hydraulic
CASSETE	SRAM GX Eagle Transmission, 10x52
CORRENTE	SRAM GX Eagle Transmission
CONJUNTO PEDALEIRO	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
CUBOS	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
RAIOS	Sapim, 28, straight pull, DBL Technology
PNEUS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Preço: 6 149,00 €

## GEOMETRIA

QUADRO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Comprimento do tubo do assento (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	262			287			312			337
Ângulo do tubo do assento	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°	76,5°	76,9°	77,2°	76,5°
Comprimento do tubo superior (mm)	558	557	556	589	588	587	622	621	621	654
Comprimento do tubo principal (mm)	100			105			115			120
Ângulo do tubo principal	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°	62,7°	63,1°	63,4°	62,7°
Garfo ancinho (mm)	44			44			44			44
Trilha (mm)	147	144	141	147	144	141	147	144	141	147
distância entre eixos (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304
Comprimento Chain Stay (mm)	445	443	442	445	443	442	445	443	442	445
Suporte inferior (mm)	29	24	19	29	24	19	29	24	19	29
Pilha (mm)	633	630	627	638	635	632	647	644	641	652
Alcançar (mm)	418	421	426	448	452	456	468	471	476	499
Altura do standover (mm)	714	718	723	733	738	742	746	750	755	762
Largura do guidão (mm)	800			800			800			800
Comprimento da haste (mm)	40			40			40			40
Comprimento da Manivela (mm)	165			170			170			170
Tamanho da roda	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.