



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	S, M, L, XL
FARBY	Mercury/Raw Carbon
RÁM	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
VIDLICA	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
TLMIČ	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
KOMPONENTY	
RIADIDLÁ	Giant Contact TR35, 800x35mm, 35mm rise
GRIPY	Giant Tactal Pro Single
PREDSTAVEC	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEDLOVKA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SEDADLO	Giant Romero SL
POHON	
RADENIE	SRAM AXS Pod, discrete clamp, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM GX Eagle Transmission
BRZDY	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
BRZDOVÉ PÁKY	TRP DH-R EVO, hydraulic
KAZETA	SRAM GX Eagle Transmission, 10x52
REŤAZ	SRAM GX Eagle Transmission
KLUKY	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NÁBOJE	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
ŠPICE	Sapim, 28, straight pull, DBL Technology
PNEUMATIKY	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
DOPLNKY	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Cena: 7 399 €

GEOMETRIA

RÁM	S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	400			425			450		
Hĺbka vloženia sedlovky (mm)	262			287			312		
Uhol sedlovej trubky	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°	76,5°	76,9°	77,2°
Dĺžka hornej rámovej trubky (mm)	558	557	556	589	588	587	622	621	621
Dĺžka hlavovej trubky (mm)	100			105			115		
Uhol hlavovej trubky	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°	62,7°	63,1°	63,4°
Offset vidlice (mm)	44			44			44		
Trail (mm)	147	144	141	147	144	141	147	144	141
Rázvor (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269
Dĺžka zadnej stavby (mm)	445	443	442	445	443	442	445	443	442
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	29	24	19	29	24	19	29	24	19
Stack - výška riadenia (mm)	633	630	627	638	635	632	647	644	641
Reach (mm)	418	421	426	448	452	456	468	471	476
Výška rámu od zeme (mm)	714	718	723	733	738	742	746	750	755
Šírka riaditok (mm)	800			800			800		
Dĺžka predstavca (mm)	40			40			40		
Dĺžka klúku (mm)	165			170			170		
Rozmer kolies	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.