

# REIGN ADVANCED 1

**GIANT**



## SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Mercury/Raw Carbon
RAM	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
GAFFEL	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
BAKDÄMPARE	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
KOMPONENTER	
STYRE	Giant Contact TR35, 800x35mm, 35mm rise
GREPPAR	Giant Tactal Pro Single
STAM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SADELSTOLPE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SADEL	Giant Romero SL
DRIVLINAN	
VÄXLAR	SRAM AXS Pod, discrete clamp, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM GX Eagle Transmission
BROMSAR	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
BROMSSPAKAR	TRP DH-R EVO, hydraulic
KASSETT	SRAM GX Eagle Transmission, 10x52
KEDJA	SRAM GX Eagle Transmission
VEVPARTI	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NAV	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
EKRAR	Sapim, 28, straight pull, DBL Technology
DÄCK	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

## GEOMETRY

RAM	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Längd sadelrör (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Vinkel sadelrör	77,5°   77,8°   78,2°	77,5°   77,8°   78,2°	76,5°   76,9°   77,2°	76,5°   76,9°   77,2°	76,5°   76,9°   77,2°	76,5°   76,9°   77,2°	76,5°   76,9°   77,2°	76,5°   76,9°   77,2°	76,5°   76,9°   77,2°	76,5°   76,9°   77,2°	76,5°   76,9°   77,2°	76,5°   76,9°   77,2°
Topprörets längd (mm)	558   557   556	589   588   587	622   621   621	654   653   653								
Styrhuvud Längd (mm)	100			105			115			120		
Vinkel styrhuvud	62,7°   63,0°   63,4°	62,7°   63,0°   63,4°	62,7°   63,1°   63,4°	62,7°   63,1°   63,4°	62,7°   63,1°   63,4°	62,7°   63,1°   63,4°	62,7°   63,1°   63,4°	62,7°   63,1°   63,4°	62,7°   63,1°   63,4°	62,7°   63,1°   63,4°	62,7°   63,1°   63,4°	62,7°   63,1°   63,4°
Gaffelvinkel (mm)	44			44			44			44		
Spår (mm)	147   144   141	147   144   141	147   144   141	147   144   141			147   144   141			147   144   141		
Hjulbas (mm)	1214   1213   1212	1246   1245   1244	1271   1270   1269	1304   1303   1303			1304   1303   1303			1304   1303   1303		
Kedjestagslängd (mm)	445   443   442	445   443   442	445   443   442	445   443   442			445   443   442			445   443   442		
Nedre fäste Drop (mm)	29   24   19	29   24   19	29   24   19	29   24   19			29   24   19			29   24   19		
Stack (mm)	633   630   627	638   635   632	647   644   641	652   649   646			652   649   646			652   649   646		
Reach (mm)	418   421   426	448   452   456	468   471   476	499   503   507			499   503   507			499   503   507		
Stå över höjden (mm)	714   718   723	733   738   742	746   750   755	762   766   771			762   766   771			762   766   771		
Styrets bredd (mm)	800			800			800			800		
Stamlängd (mm)	40			40			40			40		
Vevlängd (mm)	165			170			170			170		
Hjulstorlek	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

All specifications listed are subject to change without notice.