

# REIGN ADVANCED 2

GIANT



## SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Sangria/Carbon
RAMME	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
FORGAFFEL	Fox 38 Rhythm, 170mm, GRIP damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
BAGDÆMPER	Fox Float Performance, 205/62.5, custom tuned for Giant
KOMPONENTER	
STYR	Giant Contact TR35, 800x35mm, 20mm rise
GREB / STYRBÅND	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
FREMPIND	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SADELPIND	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SADEL	Giant Romero SL
PEDALER	platform [GC,GT]
GEARGRUPPE	
SKIFTEGREB	Shimano SLX SL-M7100, 1x12
FORSKIFTER	N/A
BAGSKIFTER	Shimano SLX RD-M7100
BREMSE	Shimano BR-MT520, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BREMSEGREB	Shimano Deore BL-MT501
KASSETTE	Shimano Deore M6100, 10x51
KÆDE	Shimano
KRANKSÆT	Shimano SLX, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant AM 29, alloy
NAV	alloy, sealed
EGER	Stainless steel
DÆK	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EKSTRA	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Pris: 44.999,00 kr.

## GEOMETRI

RAMME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sadelrørslængde (mm)	400			425			450			475		
Sadelpindindsætningsdybde (mm)	262			287			312			337		
Sadelrørvinkel	78,3°   78,7°   79,0°			78,3°   78,7°   79,0°			77,3°   77,7°   78,0°			77,3°   77,7°		
Overrørslængde (mm)	556   555   555	587   586   585	620   620   619	652   652   651	684   684   683	716   716   715	748   748   747	780   780   779	812   812   811	844   844   843	876   876   875	
Kronrørslængde (mm)	100			105			115			120		
Kronrørvinkel	63,5°   63,9°   64,2°			63,5°   63,9°   64,2°			63,5°   63,9°   64,2°			63,5°   63,9°		
Forgaffel fremspring (rake) (mm)	44			44			44			44		
Sti (mm)	140   138   135	140   138   135	140   138   135	140   138   135	140   138   135	140   138   135	140   138   135	140   138   135	140   138   135	140   138   135	140   138   135	
Akselafstand (mm)	1214   1213   1212	1246   1245   1244	1271   1270   1269	1304   1303   1302	1337   1336   1335	1370   1369   1368	1403   1402   1401	1436   1435   1434	1469   1468   1467	1502   1501   1500	1535   1534   1533	
Kædestagslængde (mm)	445   443   442	445   443   442	445   443   442	445   443   442	445   443   442	445   443   442	445   443   442	445   443   442	445   443   442	445   443   442	445   443   442	
Krankboks drop (mm)	35   30   25	35   30   25	35   30   25	35   30   25	35   30   25	35   30   25	35   30   25	35   30   25	35   30   25	35   30   25	35   30   25	
Stack (mm)	627   624   622	632   629   626	641   638   635	645   642   639	654   651   648	663   660   657	672   669   666	681   678   675	690   687   684	699   696   693	708   705   702	
Reach (mm)	426   430   434	456   460   464	476   480   484	506   510   514	526   530   534	546   550   554	566   570   574	586   590   594	606   610   614	626   630   634	646   650   654	
Skridthøjde (mm)	720   724   729	735   739   744	751   756   760	766   771   775	781   786   790	796   801   805	811   816   820	826   831   835	841   846   850	856   861   865	871   876   880	
Styrbredde (mm)	800			800			800			800		
Frempindslængde (mm)	40			40			40			40		
Pedalarmslængde (mm)	165			170			170			170		
Hjulstørrelse	29"			29"			29"			29"		

Alle de anførte specifikationer kan ændres uden varsel.