



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLOURS</b>	Sangria/Carbon
<b>FRAME</b>	Advanced-Grade Composite front and rear triangles, 160mm Maestro suspension, flip chip 3 position, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, integrated downtube storage, 55mm Chainline
<b>FORK</b>	Fox 38 Rhythm, 170mm, GRIP damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
<b>SHOCK</b>	Fox Float Performance, custom tuned for Giant
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, alloy, 35mm
<b>GRIPS</b>	Giant Tactal Pro Single lock-on
<b>STEM</b>	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
<b>SEATPOST</b>	Giant Contact Switch AT dropper, adjustable travel, remote
<b>SADDLE</b>	Giant Romero SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano SLX SL-M7100, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano SLX RD-M7100
<b>BRAKES</b>	Shimano BR-MT520, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
<b>BRAKE LEVERS</b>	Shimano Deore BL-MT501
<b>CASSETTE</b>	Shimano Deore M6100, 10x51
<b>CHAIN</b>	KMC X-12
<b>CRANKSET</b>	Shimano SLX, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant AM 29, tubeless ready sleeve-joint rim, 30mm inner width
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 3-pawl driver, 6-bolt
<b>SPOKES</b>	Stainless steel
<b>TIRES</b>	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
<b>EXTRAS</b>	Tubeless prepared, 2.5" max tyre size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

**Price: \$6,799.00**

## GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	78.3°	78.7°	79.0°	78.3°	78.7°	79.0°	77.3°	77.7°	78.0°	77.3°	77.7°	78.0°
Top Tube Length (mm)	556	555	555	587	586	585	620	620	619	652	652	651
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°	63.5°	63.9°	64.2°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Wheelbase (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Chain Stay Length (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Bottom Bracket Drop (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	639
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Stand Over Height (mm)	720	724	729	735	739	744	751	756	760	746	751	756
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29"			29"			29"			29"		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.