

REIGN ADVANCED 2



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Dried Matcha
FRAME	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
FORK	Fox 38 Rhythm, 170mm, GRIP damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float Performance, 205/62.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SADDLE	Giant Romero SL
PEDALS	
DRIVETRAIN	
SHIFTERS	Shimano SLX SL-M7100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX RD-M7100
BRAKES	Shimano BR-MT520, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BRAKE LEVERS	Shimano Deore BL-MT501
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	Shimano
CRANKSET	Shimano SLX, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant TRA WheelSystem, 6069 alloy, welded, 30mm IW, 40mm OW, 21mm H, Wide Guard technology, [F] 29, [R] 29
HUBS	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, MicroSpline driver body
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Suggested Retail Price (CDN): \$5,699.00

FRAME GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	77.5°	77.8°	78.2°	77.5°	77.8°	78.2°	76.5°	76.9°	77.2°	76.5°	76.9°	77.2°
Top Tube Length (mm)	558	557	556	589	588	587	622	621	621	654	653	653
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	62.7°	63.0°	63.4°	62.7°	63.0°	63.4°	62.7°	63.1°	63.4°	62.7°	63.1°	63.4°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	147	144	141	147	144	141	147	144	141	147	144	141
Wheelbase (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Chain Stay Length (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Bottom Bracket Drop (mm)	29	24	19	29	24	19	29	24	19	29	24	19
Stack (mm)	633	630	627	638	635	632	647	644	641	652	649	646
Reach (mm)	418	421	426	448	452	456	468	471	476	499	503	507
Stand Over Height (mm)	714	718	723	733	738	742	746	750	755	762	766	771
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

All prices and specifications are subject to change without notice.