

REIGN ADVANCED 2

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Dried Matcha
FRAME	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
FORK	Fox 38 Rhythm, 170mm, GRIP damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float Performance, 205/62.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SADDLE	Giant Romero SL
PEDALS	
DRIVETRAIN	
SHIFTERS	Shimano SLX SL-M7100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX RD-M7100
BRAKES	Shimano BR-MT520, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BRAKE LEVERS	Shimano Deore BL-MT501
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	Shimano
CRANKSET	Shimano SLX, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant TRA WheelSystem, 6069 alloy, welded, 30mm IW, 40mm OW, 21mm H, Wide Guard technology, [F] 29, [R] 29
HUBS	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, MicroSpline driver body
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Suggested Retail Price (CDN): \$5,699.00

FRAME GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Seat Tube Angle	77.5° 77.8° 78.2°			77.5° 77.8° 78.2°			76.5° 76.9° 77.2°			76.5° 76.9° 77.2°		
Top Tube Length (mm)	558 557 556			589 588 587			622 621 621			654 653 653		
Head Tube Length (mm)	100			105			115			120		
Head Tube Angle	62.7° 63.0° 63.4°			62.7° 63.0° 63.4°			62.7° 63.1° 63.4°			62.7° 63.1° 63.4°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	147 144 141			147 144 141			147 144 141			147 144 141		
Wheelbase (mm)	1214 1213 1212			1246 1245 1244			1271 1270 1269			1304 1303 1302		
Chain Stay Length (mm)	445 443 442			445 443 442			445 443 442			445 443 442		
Bottom Bracket Drop (mm)	29 24 19			29 24 19			29 24 19			29 24 19		
Stack (mm)	633 630 627			638 635 632			647 644 641			652 649 646		
Reach (mm)	418 421 426			448 452 456			468 471 476			499 503 507		
Stand Over Height (mm)	714 718 723			733 738 742			746 750 755			762 766 771		
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	165			170			170			170		
Wheel Size	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

All prices and specifications are subject to change without notice.