

REIGN ADVANCED 2



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Sangria/Carbon
FRAME	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
VOORVORK	Fox 38 Rhythm, 170mm, GRIP damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
DEMPER	Fox Float Performance, 205/62.5, custom tuned for Giant
ONDERDELEN	
STUUR	Giant Contact TR35, 800x35mm, 20mm rise
HANDVATTEN	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STUURPEN	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
ZADELPEN	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
ZADEL	Giant Romero SL
PEDALEN	platform [GC,GT]
AFMONTAGE	
SHIFTERS	Shimano SLX SL-M7100, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano SLX RD-M7100
REMMEN	Shimano BR-MT520, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
REMHENDELS	Shimano Deore BL-MT501
CASSETTE	Shimano Deore M6100, 10x51
AANDRIJVING	Shimano
CRANKSET	Shimano SLX, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant AM 29, alloy
NAVEN	alloy, sealed
SPAKEN	Stainless steel
BANDEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRA'S	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Adviesprijs: € 5.799,00

GEOMETRIE

FRAME	S			M			L			XL		
	LOW MID HIGH	LOW MID HIGH			LOW MID HIGH			LOW MID HIGH				
Zitbuis Lengte (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Zitbuis Hoek	78,3° 78,7° 79,0°			78,3° 78,7° 79,0°			77,3° 77,7° 78,0°			77,3° 77,7° 78,0°		
Frame Lengte (horizontaal) (mm)	556 555 555	587 586 585			620 620 619			652 652 651				
Balhoofdbuis Lengte (mm)	100			105			115			120		
Balhoofdbuis Hoek	63,5° 63,9° 64,2°			63,5° 63,9° 64,2°			63,5° 63,9° 64,2°			63,5° 63,9° 64,2°		
Vork Sprong (mm)	44			44			44			44		
Naloop (mm)	140 138 135			140 138 135			140 138 135			140 138 135		
Wielbasis (mm)	1214 1213 1212			1246 1245 1244			1271 1270 1269			1304 1303 1302		
Liggende achtervork lengte (mm)	445 443 442	445 443 442			445 443 442			445 443 442				
Bottom Bracket Drop (mm)	35 30 25			35 30 25			35 30 25			35 30 25		
Stack (mm)	627 624 622			632 629 626			641 638 635			645 642 639		
Reach (mm)	426 430 434			456 460 464			476 480 484			506 510 514		
Stand Over Height (mm)	720 724 729			735 739 744			751 756 760			746 751 756		
Stuur breedte (mm)	800			800			800			800		
Stuurpen Lengte (mm)	40			40			40			40		
Cranklengte (mm)	165			170			170			170		
Wielmaat	29"			29"			29"			29"		

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.