

REIGN ADVANCED 2

GIANT



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Sangria/Carbon
RAM	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
GAFFEL	Fox 38 Rhythm, 170mm, GRIP damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
BAKDÄMPARE	Fox Float Performance, 205/62.5, custom tuned for Giant
KOMPONENTER	
STYRE	Giant Contact TR35, 800x35mm, 20mm rise
GREPPAR	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STAM	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SADELSTOLPE	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SADEL	Giant Romero SL
PEDALER	platform [GC,GT]
DRIVLINA	
VÄXLAR	Shimano SLX SL-M7100, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	Shimano SLX RD-M7100
BROMSAR	Shimano BR-MT520, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BROMSSPAKAR	Shimano Deore BL-MT501
KASSETT	Shimano Deore M6100, 10x51
KEDJA	Shimano
VEVPARTI	Shimano SLX, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant AM 29, alloy
NAV	alloy, sealed
EKRAR	Stainless steel
DÄCK	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Price: 68 290,00 kr

GEOMETRY

RAM	S	M	L
Längd sadelrör (mm)	LOW MID HIGH 400	LOW MID HIGH 425	LOW MID HIGH 450
Seat Post Insertion Depth (mm)	262	287	312
Vinkel sadelrör	78,3° 78,7° 79,0°	78,3° 78,7° 79,0°	77,3° 77,7° 78,0°
Topprörets längd (mm)	556 555 555	587 586 585	620 620 619
Styrhuvud Längd (mm)	100	105	115
Vinkel styrhuvud	63,5° 63,9° 64,2°	63,5° 63,9° 64,2°	63,5° 63,9° 64,2°
Gaffelvinkel (mm)	44	44	44
Spår (mm)	140 138 135	140 138 135	140 138 135
Hjulbas (mm)	1214 1213 1212	1246 1245 1244	1271 1270 1269
Kedjestagslängd (mm)	445 443 442	445 443 442	445 443 442
Nedre fäste Drop (mm)	35 30 25	35 30 25	35 30 25
Stack (mm)	627 624 622	632 629 626	641 638 635
Reach (mm)	426 430 434	456 460 464	476 480 484
Stå över höjden (mm)	720 724 729	735 739 744	751 756 760
Styrets bredd (mm)	800	800	800
Stamlängd (mm)	40	40	40
Vevlängd (mm)	165	170	170
Hjulstorlek	29"	29"	29"

All specifications listed are subject to change without notice.