

REIGN ADVANCED



SPECIFIKACE

RÁM	
VELIKOSTI	S, M, L, XL
BARVA	Luminous Lagoon/Chrome
RÁM	Advanced Composite front and rear triangles, 160mm Maestro Suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
VIDLICE	RockShox Zeb Ultimate, Charger 3.2, RC2 damper, 170 mm, DebonAir, 15x110 mm Maxle Stealth
TLUMIČ	RockShox Vivid Ultimate RC2T, adjustable hydraulic bottom out, trunnion mount, 205/65
KOMPONENTY	
ŘÍDÍTKA	Giant Contact TR35, 800x35mm, 35mm rise
GRIPY	Giant Tactal Pro Single
PŘEDSTAVEC	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SEDOVKA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDLO	Giant Romero SL
OSAZENÍ	
ŘAZENÍ	SRAM AXS Pod, 1x12
PŘEHAZOVAČKA	SRAM GX AXS Transmission
BRZDY	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
BRZDOVÉ PÁKY	TRP EVO Pro
KAZETA	SRAM GX Eagle Transmission, 10x52
ŘETĚZ	SRAM GX Eagle Transmission
KLIKY	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
STŘED	SRAM DUB, press fit

KOLA	
RÁFKY	Giant TRA WheelSystem, 6069 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NÁBOJE	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, XD driver body
DRÁTY	Sapim, 28, straight pull, DBL Technology
PLÁŠTĚ	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, MaxxTerra, DD, TR tubeless
DOPLŇKY	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

Cena: 179 999 Kč

GEOMETRIE

RÁM	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Délka sedlové trubky (mm)	400			425			450			475		
Max. zasunutí sedlovky (mm)	262			287			312			337		
Úhel sedlové trubky	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°	76,5°	76,9°	77,2°	76,5°	76,9°	77,2°
Délka horní trubky (mm)	558	557	556	589	588	587	622	621	621	654	653	653
Délka hlavové trubky (mm)	100			105			115			120		
Úhel hlavové trubky	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°	62,7°	63,1°	63,4°	62,7°	63,1°	63,4°
Offset vidlice (mm)	44			44			44			44		
Trail (mm)	147	144	141	147	144	141	147	144	141	147	144	141
Rozvor (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Délka řetězové vzpěry (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Bottom Bracket Drop (mm)	29	24	19	29	24	19	29	24	19	29	24	19
Stack (mm)	633	630	627	638	635	632	647	644	641	652	649	646
Reach (mm)	418	421	426	448	452	456	468	471	476	499	503	507
Výška rámu od země (mm)	714	718	723	733	738	742	746	750	755	762	766	771
Šířka řídicíků (mm)	800			800			800			800		
Délka představce (mm)	40			40			40			40		
Délka klik (mm)	165			170			170			170		
Rozměr kol	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Děláme vše pro to, aby veškeré údaje na tomto webu byly správné a aktuální. Přesto si ale musíme vyhradit právo na případné změny specifikací, barevného provedení a cen, a to bez předchozího upozornění. Děkujeme za pochopení.