

REIGN ADVANCED E+ 0

GIANT



SPECS

| HYBRID CYCLING TECHNOLOGY |                                                                                                         |
|---------------------------|---------------------------------------------------------------------------------------------------------|
| MOTOR                     | Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio                                  |
| CONTROLLER                | Giant RideControl Ergo 4                                                                                |
| DISPLAY                   | Giant RideControl Go Lux                                                                                |
| BATTERY                   | iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender                         |
| CHARGER                   | Giant EnergyPak 4A Charger, 48V                                                                         |
| FRAME                     |                                                                                                         |
| FRAME                     | Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system |
| FORK                      | Fox 38 Factory, 29", 180mm travel, GripX2 damper, 44mm offset, KoboltX2 110x15mm Boost axle             |
| SHOCK                     | Fox Float X2 Factory, 205x65mm, 2-position lever, HSC, LSC, HSR   LSR, custom tuned                     |
| COMPONENTS                |                                                                                                         |
| HANDLEBAR                 | Giant Contact SL TR35, 35mm rise, 5-degree upsweep, 9-degree backsweep, 35x800mm                        |
| GRIPS                     | Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)                                 |
| STEM                      | Giant Contact SL 35, 40 mm                                                                              |
| SEATPOST                  | Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm      |
| SADDLE                    | Giant Romero, neutral                                                                                   |
| DRIVETRAIN                |                                                                                                         |
| SHIFTERS                  | SRAM AXS Pod Rocker, discrete clamp                                                                     |
| FRONT DERAILLEUR          | SRAM XO AXS Eagle, Transmission, T-Type                                                                 |
| REAR DERAILLEUR           | SRAM XO AXS Eagle, Transmission, T-Type                                                                 |
| BRAKES                    | TRP EVO Pro, hydraulic disc, 4-piston, 220mm [F/R]                                                      |
| BRAKE LEVERS              | TRP EVO Pro                                                                                             |
| CASSETTE                  | SRAM Eagle Transmission, 10x52, 12-speed                                                                |
| CHAIN                     | SRAM Eagle Transmission, Flattop, PowerLink, 12-speed                                                   |
| CRANKSET                  | Praxis Carbon e-crank arms, Q-factor: 168mm, length: 155mm                                              |

| WHEELS                      |                                                                                                                               |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| RIMS                        | Giant e-TRA, hookless, 30mm inner width, Wide Guard                                                                           |
| HUBS                        | Giant e-TRA, E-Drive 260Nm 6-pawl driver, 72t engagement, 15x110mm [F] 12x148mm [R], e-bike optimized                         |
| SPOKES                      | Sapim Race [F] E-Lite [R], e-bike optimized, Dynamic Balanced Lacing                                                          |
| TYRES                       | Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R] |
| EXTRAS                      | Aegis Tire Checker, BLE+ tire pressure monitoring system tubeless kit (liquid, valves, levers, manual, tool)                  |
| ACCESSORIES                 |                                                                                                                               |
| LIGHTING                    | Optional: Giant Recon series e-bike lights available and direct-connect compatible                                            |
| LIMITS                      |                                                                                                                               |
| COMBINED MAXIMUM LOAD LIMIT | 156kg                                                                                                                         |

Price: €10,199.00

GEOMETRY

| FRAME                  | S                     |               | M             |       | L                     |               | XL                    |               |
|------------------------|-----------------------|---------------|---------------|-------|-----------------------|---------------|-----------------------|---------------|
|                        | LOW                   | HIGH          | LOW           | HIGH  | LOW                   | HIGH          | LOW                   | HIGH          |
| Seat Tube Angle        | 77.1°                 | 77.5°   77.9° | 77.5°         | 77.9° | 77.1°                 | 77.5°   77.9° | 77.1°                 | 77.5°   77.9° |
| Top Tube Length (mm)   | 570   569   568       |               | 601   600     |       | 625   624   623       |               | 657   656   655       |               |
| Head Tube Length (mm)  | 95                    |               | 105           |       | 120                   |               | 135                   |               |
| Head Tube Angle        | 63.1°   63.5°   63.9° |               | 63.5°   63.9° |       | 63.1°   63.5°   63.9° |               | 63.1°   63.5°   63.9° |               |
| Wheelbase (mm)         | 1226   1226   1227    |               | 1261   1261   |       | 1287   1288   1288    |               | 1323   1323   1324    |               |
| Chain Stay Length (mm) | 450   450   450       |               | 450   450     |       | 450   450   450       |               | 450   450   450       |               |
| Stack (mm)             | 647   645   642       |               | 654   651     |       | 669   667   665       |               | 683   680   678       |               |
| Reach (mm)             | 426   430   435       |               | 460   465     |       | 476   480   485       |               | 505   510   514       |               |
| Crank Length (mm)      | 155                   |               | 155           |       | 155                   |               | 155                   |               |

All specifications listed are subject to change without notice.