

REIGN ADVANCED E+ 0

GIANT



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
MANDO	Giant RideControl Ergo 4
PANTALLA	Giant RideControl GO Lux
BATERÍA	Giant EnergyPak Smart 560Wh, integrated, 48V, Giant EnergyPak Plus 280 range extender
CARGADOR	Giant EnergyPak smart charger 4A, 48V
CONECTIVIDAD	Aegis Tire Checker included in RideControl display
CUADRO	
TALLAS	S, M, L, XL
COLORES	Purple Haze/Metallic Navy
CUADRO	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
HORQUILLA	Fox 38 Factory, 29", 180mm travel, Grip X2 damper, 44mm offset, KaboltX 110x15mm Boost axle
AMORTIGUADOR	Fox Float X2 Factory, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
COMPONENTES	
MANILLAR	Giant Contact SLR Trail, integrated carbon 1-piece handlebar 800mm 35mm rise, 40/45/50mm Reach Adjust, +3/0/-3degree Angle Adjust System
PUÑOS	Giant Tactal Pro-E, tapered design, 135mm Ø28–30mm (S/M) 142mm Ø29–32mm (L/XL)
POTENCIA	Giant Contact SLR Trail, integrated carbon 1-piece handlebar, 40/45/50mm Reach Adjust, +3/0/-3degree Angle Adjust System
TIJA DE SILLÍN	Fox Transfer Factory, 30.9mm, MMX remote
SILLÍN	Giant Romero SL, Neutral
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS POD Rocker Paddle
CAMBIO TRASERO	SRAM XX Eagle Transmission AXS
FRENOS	SRAM Maven Ultimate, 4-piston, 200mm CenterLine [F/R]
PALANCAS DE FRENOS	SRAM Maven Ultimate Stealth
CASETTE	SRAM XO Eagle Transmission, 10-52T, 12-speed
CADENA	SRAM XO Eagle Transmission Flattop Powerlock 12-speed
JGO. PLATOS Y BIELAS	SRAM XX Eagle Transmission Direct Mount E-MTB Chainring 36T Praxis Carbon e-crank arms (Q-Factor:168mm, Length: 160mm)

RUEDAS	
LLANTAS	Giant TRX Carbon, 30mm inner width, Wide Side Wall Design for improved strength and flat protection
BUJES	Giant TRX, E-Drive 260Nm 6-Pawl Driver, 72T engagement, XD body, 15x110mm [F] 12x148mm [R], e-bike optimized
RADIOS	Giant TRX, Dynamic Balanced Lacing
CUBIERTAS	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAS	Aegis Tire Checker
ACCESORIOS	
LUCES	Optional: - Giant Recon series e-bike lights available and direct connectable

Precio: 10.999,00 €

GEOMETRÍA

CUADRO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	
Longitud del tubo del sillín (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	235			260			285			310
Ángulo del tubo del sillín	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°
Longitud del tubo superior (mm) (mm)	570	569	568	602	601	600	625	624	623	650
Longitud del tubo de dirección (mm) (mm)	95			105			120			130
Ángulo del tubo de dirección	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°
Inclinación de la horquilla (mm)	44			44			44			44
Trail (mm) (mm)	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4	133,3
Distancia entre ejes (mm) (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1313
Longitud de la vaina (mm) (mm)	450	450	450	450	450	450	450	450	450	450
Caída del eje de pedalier (mm) (mm)	10	5		10	5		10	5		10
Stack (mm) (mm)	647	645	642	656	654	651	669	667	665	680
Reach (mm) (mm)	426	430	435	456	460	465	476	480	485	500
Ancho del manillar (mm) (mm)	800			800			800			800
Longitud de la potencia (mm) (mm)	40			40			40			40
Longitud de las bielas (mm) (mm)	160			160			160			160
Tamaño de ruedas	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5"

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.