

REIGN ADVANCED E+ 0

GIANT



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Pro3, 48v, 90Nm, 800W max power, 400% max support ratio
COMMANDE	Giant RideControl Ergo 4
ECRAN	Giant RideControl GO Lux
BATTERIE	Giant EnergyPak Smart 560Wh, integrated, 48V
ENERGYPAK PLUS COMPATIBLES	Giant EnergyPak Plus 280 range extender (included)
CHARGEUR	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITÉ	Tire Checker Aegis, E-Lock, FindMyBike
CADRE	
TAILLES	S, M, L, XL
COLORIS	Purple Haze/Metallic Navy
CADRE	Advanced-grade composite frame, Advanced forged composite upper rocker and internal link, 170mm Maestro suspension system
FOURCHE	Fox 38 Factory, 29", 180mm travel, Grip X2 damper, 44mm offset, KaboltX 110x15mm Boost axle
AMORTISSEUR	Fox Float X2 Factory, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
COMPOSANTS	
CINTRE	Giant Contact SLR Trail, integrated carbon 1-piece handlebar 800mm 35mm rise, 40/45/50mm Reach Adjust, +3/0/-3degree Angle Adjust System
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SLR Trail, integrated carbon 1-piece handlebar, 40/45/50mm Reach Adjust, +3/0/-3degree Angle Adjust System
TIGE DE SELLE	Fox Transfer Factory, 30.9mm, MMX remote
SELLE	Giant Romero SL, Neutral
DÉRAILLEUR	
MANETTES	SRAM AXS POD Rocker Paddle
DÉRAILLEUR ARRIÈRE	SRAM XX Eagle Transmission AXS
FREINS	SRAM Maven Ultimate, 4-piston, 200mm CenterLine [F/R]
LEVIERS DE FREIN	SRAM Maven Ultimate Stealth
CASSETTE	SRAM XO Eagle Transmission, 10-52T, 12-speed
CHAÎNE	SRAM XO Eagle Transmission Flattop Powerlock 12-speed
PÉDALIER	SRAM XX Eagle Transmission Direct Mount E-MTB Chainring 36T Praxis Carbon e-crank arms (Q-Factor:168mm, Length: 160mm)

ROUES	
JANTES	Giant TRX Carbon, 30mm inner width, Wide Side Wall Design for improved strength and flat protection
MOYEURS	Giant TRX, E-Drive 260Nm 6-Pawl Driver, 72T engagement, XD body, 15x110mm [F] 12x148mm [R], e-bike optimized
RAYONS	Giant TRX, Dynamic Balanced Lacing
PNEUS	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles (éclairages e-bike Recon disponible et directement connectable)

Prix Public Conseillé: 11 500,00 €

GÉOMÉTRIE

CADRE	S			M			L			XL	
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	N
Longueur de tube de selle (mm)	400			425			450			475	
Seat Post Insertion Depth (mm)	235			260			285			310	
Angle de tube de selle	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	7
Longueur du tube supérieur (mm)	570	569	568	602	601	600	625	624	623	657	65
Longueur du tube de direction (mm)	95			105			120			135	
Angle du tube de direction	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	6
Déport de fourche (mm)	44			44			44			44	
Trail (mm)	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4	133,3	1
Empattement (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1323	1
Longueur des bases (mm)	450	450	450	450	450	450	450	450	450	450	45
Drop du boîtier de pédalier (mm)	10	5		10	5		10	5		10	5
Stack (mm)	647	645	642	656	654	651	669	667	665	683	68
Reach (mm)	426	430	435	456	460	465	476	480	485	505	51
Largeur de cintre (mm)	800			800			800			800	
Longueur de potence (mm)	40			40			40			40	
Longueur des manivelles (mm)	160			160			160			160	
Diamètre des roues	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" /	

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.