

REIGN ADVANCED E+ 0

GIANT



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio
OVLÁDAČ	Giant RideControl Ergo 4
OVLÁDACIA JEDNOTKA	Giant RideControl Go Lux
BATÉRIA	iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
NABÍJAČKA	Giant EnergyPak 4A Charger, 48V
RÁM	
RÁM	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
VIDLICA	Fox 38 Factory, 29", 180mm travel, GripX2 damper, 44mm offset, KoboltX2 110x15mm Boost axle
TLMIČ	Fox Float X2 Factory, 205x65mm, 2-position lever, HSC, LSC, HSR LSR, custom tuned
KOMPONENTY	
RIADIDLÁ	Giant Contact SL TR35, 35mm rise, 5-degree upsweep, 9-degree backsweep, 35x800mm
GRIPY	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
PREDSTAVEC	Giant Contact SL 35, 40 mm
SEDLOVKA	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SEDADLO	Giant Romero, neutral
POHON	
RADENIE	SRAM AXS Pod Rocker, discrete clamp
PREŠMYKAČ	SRAM XO AXS Eagle, Transmission, T-Type
PREHADZOVAČKA	SRAM XO AXS Eagle, Transmission, T-Type
BRZDY	TRP EVO Pro, hydraulic disc, 4-piston, 220mm [F/R]
BRZDOVÉ PÁKY	TRP EVO Pro
KAZETA	SRAM Eagle Transmission, 10x52, 12-speed
REŤAZ	SRAM Eagle Transmission, Flattop, PowerLink, 12-speed
KLUKY	Praxis Carbon e-crank arms, Q-factor: 168mm, length: 155mm

KOLESÁ	
RÁFIKY	Giant e-TRA, hookless, 30mm inner width, Wide Guard
NÁBOJE	Giant e-TRA, E-Drive 260Nm 6-pawl driver, 72t engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
ŠPICE	Sapim Race [F] E-Lite [R], e-bike optimized, Dynamic Balanced Lacing
PNEUMATIKY	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
DOPLNKY	Aegis Tire Checker, BLE+ tire pressure monitoring system tubeless kit (liquid, valves, levers, manual, tool)
PRÍSLUŠENSTVO	
OSVETLENIE	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITY	
COMBINED MAXIMUM LOAD LIMIT	156kg

Cena: 10 199 €

GEOMETRIA

RÁM	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Uhol sedlovej trubky	77,1°	77,5°	77,9°	77,5°	77,9°	77,1°	77,5°	77,9°
Dĺžka hornej rámovej trubky (mm)	570	569	568	601	600	625	624	623
Dĺžka hlavovej trubky (mm)	95			105	120			135
Uhol hlavovej trubky	63,1°	63,5°	63,9°	63,5°	63,9°	63,1°	63,5°	63,9°
Rázvor (mm)	1226	1226	1227	1261	1261	1287	1288	1288
Dĺžka zadnej stavby (mm)	450	450	450	450	450	450	450	450
Stack - výška riadenia (mm)	647	645	642	654	651	669	667	665
Reach (mm)	426	430	435	460	465	476	480	485
Dĺžka klúk (mm)	155			155	155			155

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.