

REIGN ADVANCED E+ 0

GIANT



SPECIFIKACIJE

| HIBRIDNA GONILNA TEHNOLOGIJA |                                                                                                         |
|------------------------------|---------------------------------------------------------------------------------------------------------|
| MOTOR                        | Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio                                  |
| TIPALO                       | Giant RideControl Ergo 4                                                                                |
| PRIKAZOVALNIK                | Giant RideControl Go Lux                                                                                |
| BATERIJA                     | iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender                         |
| CHARGER                      | Giant EnergyPak 4A Charger, 48V                                                                         |
| OKVIR                        |                                                                                                         |
| OKVIR                        | Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system |
| VILICE                       | Fox 38 Factory, 29", 180mm travel, GripX2 damper, 44mm offset, KoboltX2 110x15mm Boost axle             |
| AMORTIZER                    | Fox Float X2 Factory, 205x65mm, 2-position lever, HSC, LSC, HSR   LSR, custom tuned                     |
| KOMPONENTE                   |                                                                                                         |
| KRMILO                       | Giant Contact SL TR35, 35mm rise, 5-degree upsweep, 9-degree backsweep, 35x800mm                        |
| GRIPS                        | Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)                                 |
| OPORA KRMILA                 | Giant Contact SL 35, 40 mm                                                                              |
| OPORA SEDEŽA                 | Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm      |
| SEDEŽ                        | Giant Romero, neutral                                                                                   |
| POGON                        |                                                                                                         |
| PRESTAVNE ROČICE             | SRAM AXS Pod Rocker, discrete clamp                                                                     |
| PREDNJI MENJALNIK            | SRAM XO AXS Eagle, Transmission, T-Type                                                                 |
| ZADNJI MENJALNIK             | SRAM XO AXS Eagle, Transmission, T-Type                                                                 |
| ZAVORE                       | TRP EVO Pro, hydraulic disc, 4-piston, 220mm [F/R]                                                      |
| ZAVORNE ROČICE               | TRP EVO Pro                                                                                             |
| VERIŽNIK                     | SRAM Eagle Transmission, 10x52, 12-speed                                                                |
| VERIGA                       | SRAM Eagle Transmission, Flattop, PowerLink, 12-speed                                                   |
| GONILKE Z VERIŽNIKI          | Praxis Carbon e-crank arms, Q-factor: 168mm, length: 155mm                                              |

| OBROČNIKI                   |                                                                                                                               |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| OBROČI                      | Giant e-TRA, hookless, 30mm inner width, Wide Guard                                                                           |
| PESTA                       | Giant e-TRA, E-Drive 260Nm 6-pawl driver, 72t engagement, 15x110mm [F] 12x148mm [R], e-bike optimized                         |
| NAPERE                      | Sapim Race [F] E-Lite [R], e-bike optimized, Dynamic Balanced Lacing                                                          |
| PLAŠČI                      | Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R] |
| DODATKI                     | Aegis Tire Checker, BLE+ tire pressure monitoring system tubeless kit (liquid, valves, levers, manual, tool)                  |
| DODATNA OPREMA              |                                                                                                                               |
| SVETILA                     | Optional: Giant Recon series e-bike lights available and direct-connect compatible                                            |
| LIMITS                      |                                                                                                                               |
| COMBINED MAXIMUM LOAD LIMIT | 156kg                                                                                                                         |

GEOMETRIJA

| OKVIR                                        | S             |  | M             |  | L             |  | XL            |  |
|----------------------------------------------|---------------|--|---------------|--|---------------|--|---------------|--|
|                                              | LOW   HIGH    |  | LOW   HIGH    |  | LOW   HIGH    |  | LOW   HIGH    |  |
| Kot sedežne cevi                             | 77,1°   77,5° |  | 77,9°   77,5° |  | 77,1°   77,5° |  | 77,9°   77,1° |  |
| Top Tube Length (mm)                         | 570   569     |  | 568   601     |  | 600   625     |  | 624   623     |  |
| Višina glave okvirja (mm)                    | 95            |  | 105           |  | 120           |  | 135           |  |
| Krmilni kot                                  | 63,1°   63,5° |  | 63,9°   63,5° |  | 63,9°   63,1° |  | 63,5°   63,9° |  |
| Medosna razdalja (mm)                        | 1226   1226   |  | 1227   1261   |  | 1261   1287   |  | 1288   1288   |  |
| Dolžina cevi ob verigi (mm)                  | 450   450     |  | 450   450     |  | 450   450     |  | 450   450     |  |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 647   645     |  | 642   654     |  | 651   669     |  | 667   665     |  |
| Doseg (mm)                                   | 426   430     |  | 435   460     |  | 465   476     |  | 480   485     |  |
| Dolžina gonilke (mm)                         | 155           |  | 155           |  | 155           |  | 155           |  |

Vse navedene specifikacije se lahko spremenijo brez obvestila.