



СПЕЦИФИКАЦИИ

ХИБРИДНА ТЕХНОЛОГИЯ ЗА КОЛОЕЗДЕНЕ	
МОТОР	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
КОНТРОЛЕР	Giant RideControl Ergo 4
ДИСПЛЕЙ	Giant RideControl GO Lux
БАТЕРИЯ	Giant EnergyPak Smart 560Wh, integrated, 48V
ЗАРЯДНО	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
РАМКА	
РАЗМЕР	S, M, L, XL
ЦВЯТ	Mercury/Carbon Smoke
РАМКА	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
ВИЛКА	Fox 38 Performance Elite, 29", 180mm travel, Grip X2 damper, 44mm offset, KaboltX 110x15mm Boost axle
ЗАДЕН АМОРТИСЬОР	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SL TR35, 35x800mm, 35mm rize, Up: 5° Back: 9°
ГРИПОВЕ	Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
ЛАПА	Giant Contact SL 35
КОЛЧЕ ЗА СЕДАЛКА	Giant Contact Switch adjustable dropper, 30,9mm (S:110~140, M:140~170, L/XL: 170~200) MMX remote
СЕДАЛКА	Giant Romero, Neutral
DRIVETRAIN	
КОМАНДИ	SRAM Eagle 90 Transmission Single Click
ЗАДЕН ДЕРАЙЛЬОР	SRAM 90 Eagle Transmission
СПИРАЧКИ	TRP DH-R EVO, hydraulic disc, E2.3 caliper, 4-piston, 220mm [F/R]
РЪКОХВАТКИ ЗА СПИРАЧКИ	TRP DH-R EVO
КАСЕТА	SRAM Eagle Transmission, 10-52T, 12-speed
ВЕРИГА	SRAM 70 Eagle Transmission Flattop Powerlink 12-speed
КУРБЕЛ	SRAM Eagle Transmission 36T chainring Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

КАПЛИ	
ШИНИ	Giant e-TRA, Hookless, 30mm inner width, Hollow Side-Wall Design for improved strength and flat protection, 2~4psi lower air pressure recommended
ГЛАВИНИ	Giant e-TRA, E-Drive 260Nm 6-Pawl Driver, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
СПИЦИ	Giant TRA, Dynamic Balanced Lacing
ГУМИ	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
ЕКСТРИ	Aegis Tire Checker
АКСЕСОАРИ	
СВЕТЛИНИ	Optional: - Giant Recon series e-bike lights available and direct connectable

ГЕОМЕТРИЯ

РАМКА	S	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Seat Tube Angle	77,1° 77,5° 77,9°	77,1° 77,5° 77,9°	77,1° 77,5° 77,9°	77,1° 77,5° 77,9°
Top Tube Length (mm)	570 569 568	602 601 600	625 624 623	657 656 655
Head Tube Length (mm)	95	105	120	135
Head Tube Angle	63,1° 63,5° 63,9°	63,1° 63,5° 63,9°	63,1° 63,5° 63,9°	63,1° 63,5° 63,9°
Fork Rake (mm)	44	44	44	44
Trail (mm)	133,3 130,3 127,4	133,3 130,3 127,4	133,3 130,3 127,4	133,3 130,3 127,4
Wheelbase (mm)	1226 1226 1227	1261 1261 1261	1287 1288 1288	1323 1323 1323
Chain Stay Length (mm)	450 450 450	450 450 450	450 450 450	450 450 450
Bottom Bracket Drop (mm)	10 5	10 5	10 5	10 5
Stack (mm)	647 645 642	656 654 651	669 667 665	683 680 677
Обсер (mm)	426 430 435	456 460 465	476 480 485	505 510 515
Ширина на Кормило (mm)	800	800	800	800
Дължина на Лапа (mm)	40	40	40	40
Дължина на Курбел (mm)	160	160	160	160
Размер на Каплите	R27.5" / F29"	R27.5" / F29"	R27.5" / F29"	R27.5" / F29"

All specifications listed are subject to change without notice.