

REIGN ADVANCED E+ 1



SPECIFIKACE

HYBRIDNÍ TECHNOLOGIE	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
OVLÁDACÍ JEDNOTKA	Giant RideControl Ergo 4
DISPLEJ	Giant RideControl GO Lux
BATERIE	Giant EnergyPak Smart 560Wh, integrated, 48V
NABÍJEČKA	Giant EnergyPak smart charger 4A, 48V
KONEKTIVITA	Aegis Tire Checker included in RideControl display
RÁM	
VELIKOSTI	S, M, L, XL
BARVA	Mercury/Carbon Smoke
RÁM	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
VIDLICE	Fox 38 Performance Elite, 29", 180mm travel, Grip X2 damper, 44mm offset, KaboltX 110x15mm Boost axle
TLUMIČ	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
KOMPONENTY	
ŘÍDÍTKA	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
GRIPY	Giant Tactal Pro-E, tapered design, 135mm Ø28–30mm (S/M) 142mm Ø29–32mm (L/XL)
PŘEDSTAVEC	Giant Contact SL 35
SEDLOVKA	Giant Contact Switch adjustable dropper, 30,9mm (S:110–140, M:140–170, L/XL: 170–200) MMX remote
SEDLO	Giant Romero, Neutral
OSAZENÍ	
ŘAZENÍ	SRAM Eagle 90 Transmission Single Click
PŘEHAZOVAČKA	SRAM 90 Eagle Transmission
BRZDY	TRP DH-R EVO, hydraulic disc, E2.3 caliper, 4-piston, 220mm [F/R]
BRZDOVÉ PÁKY	TRP DH-R EVO
KAZETA	SRAM Eagle Transmission, 10-52T, 12-speed
ŘETĚZ	SRAM 70 Eagle Transmission Flattop Powerlink 12-speed
KLIKY	SRAM Eagle Transmission 36T chainring Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

KOLA	
RÁFKY	Giant e-TRA, Hookless, 30mm inner width, Hollow Side-Wall Design for improved strength and flat protection, 2~4psi lower air pressure recommended
NÁBOJE	Giant e-TRA, E-Drive 260Nm 6-Pawl Driver, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
DRÁTY	Giant TRA, Dynamic Balanced Lacing
PLÁŠTĚ	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
DOPLŇKY	Aegis Tire Checker
PŘÍSLUŠENSTVÍ	
SVĚTLO	Optional: - Giant Recon series e-bike lights available and direct connectable

Cena: 208 999 Kč

GEOMETRIE

RÁM	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Délka sedlové trubky (mm)	400			425			450			475		
Max. zasunutí sedlovky (mm)	235			260			285			310		
Úhel sedlové trubky	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°
Délka horní trubky (mm)	570	569	568	602	601	600	625	624	623	657	656	655
Délka hlavové trubky (mm)	95			105			120			135		
Úhel hlavové trubky	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°
Offset vidlice (mm)	44			44			44			44		
Trail (mm)	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4
Rozvor (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1323	1323	1323
Délka řetězové vzpěry (mm)	450	450	450	450	450	450	450	450	450	450	450	450
Bottom Bracket Drop (mm)	10	5		10	5		10	5		10	5	
Stack (mm)	647	645	642	656	654	651	669	667	665	683	680	678
Reach (mm)	426	430	435	456	460	465	476	480	485	505	510	514
Šířka řídítek (mm)	800			800			800			800		
Délka představce (mm)	40			40			40			40		
Délka klik (mm)	160			160			160			160		
Rozměr kol	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

Děláme vše pro to, aby veškeré údaje na tomto webu byly správné a aktuální. Přesto si ale musíme vyhradit právo na případné změny specifikací, barevného provedení a cen, a to bez předchozího upozornění. Děkujeme za pochopení.