

# REIGN ADVANCED E+ 1



## SPECS

| HYBRID CYCLING TECHNOLOGY |                                                                                                         |
|---------------------------|---------------------------------------------------------------------------------------------------------|
| MOTOR                     | Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology                                               |
| CONTROLLER                | Giant RideControl Ergo 4                                                                                |
| DISPLAY                   | Giant RideControl GO Lux                                                                                |
| BATTERY                   | Giant EnergyPak Smart 560Wh, integrated, 48V                                                            |
| CHARGER                   | Giant EnergyPak smart charger 4A, 48V                                                                   |
| CONNECTIVITY              | Aegis Tire Checker included in RideControl display                                                      |
| ΣΚΕΛΕΤΟΣ                  |                                                                                                         |
| ΜΕΓΕΘΗ                    | S, M, L, XL                                                                                             |
| ΧΡΩΜΑΤΑ                   | Mercury/Carbon Smoke                                                                                    |
| ΣΚΕΛΕΤΟΣ                  | Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system |
| ΠΙΠΟΥΝΙ                   | Fox 38 Performance Elite, 29", 180mm travel, Grip X2 damper, 44mm offset, KaboltX 110x15mm Boost axle   |
| ΑΝΑΡΤΗΣΗ                  | Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned                |
| ΕΞΑΡΤΗΜΑΤΑ                |                                                                                                         |
| ΤΙΜΟΝΙ                    | Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°                                             |
| GRIPS                     | Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)                          |
| ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ           | Giant Contact SL 35                                                                                     |
| ΛΑΙΜΟΣ ΣΤΕΛΛΑΣ            | Giant Contact Switch adjustable dropper, 30,9mm (S:110~140, M:140~170, L/XL: 170~200) MMX remote        |
| ΣΤΕΛΛΑ                    | Giant Romero, Neutral                                                                                   |
| ΜΕΤΑΔΟΣΗ                  |                                                                                                         |
| ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ           | SRAM Eagle 90 Transmission Single Click                                                                 |
| ΝΤΕΡΑΓΓΙΕΡ ΟΠΙΣΘΙΟ.       | SRAM 90 Eagle Transmission                                                                              |
| ΦΡΕΝΑ                     | TRP DH-R EVO, hydraulic disc, E2.3 caliper, 4-piston, 220mm [F/R]                                       |
| ΜΑΝΕΤΤΕΣ ΦΡΕΝΩΝ           | TRP DH-R EVO                                                                                            |
| CASETTE Η ΕΛΕΥΘΕΡΟ        | SRAM Eagle Transmission, 10-52T, 12-speed                                                               |
| ΑΛΥΣΙΔΑ                   | SRAM 70 Eagle Transmission Flattop Powerlink 12-speed                                                   |
| ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ            | SRAM Eagle Transmission 36T chainring Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)   |

| WHEELS      |                                                                                                                                                           |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| ΣΤΕΦΑΝΙΑ    | Giant e-TRA, Hookless, 30mm inner width, Hollow Side-Wall Design for improved strength and flat protection, 2~4psi lower air pressure recommended         |
| ΚΕΝΤΡΑ      | Giant e-TRA, E-Drive 260Nm 6-Pawl Driver, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized                                                     |
| ΑΚΤΙΝΕΣ     | Giant TRA, Dynamic Balanced Lacing                                                                                                                        |
| ΕΛΑΣΤΙΚΑ    | Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R] |
| EXTRAS      | Aegis Tire Checker                                                                                                                                        |
| ACCESSORIES |                                                                                                                                                           |
| LIGHTING    | Optional: - Giant Recon series e-bike lights available and direct connectable                                                                             |

## ΓΕΩΜΕΤΡΙΑ

| ΣΚΕΛΕΤΟΣ                       | S                     | M                     | L                     | XL                    |
|--------------------------------|-----------------------|-----------------------|-----------------------|-----------------------|
|                                | LOW   MID   HIGH      | LOW   MID   HIGH      | LOW   MID   HIGH      | LOW   MID   HIGH      |
| Seat Tube Length (mm)          | 400                   | 425                   | 450                   | 475                   |
| Seat Post Insertion Depth (mm) | 235                   | 260                   | 285                   | 310                   |
| Seat Tube Angle                | 77,1°   77,5°   77,9° | 77,1°   77,5°   77,9° | 77,1°   77,5°   77,9° | 77,1°   77,5°   77,9° |
| Top Tube Length (mm)           | 570   569   568       | 602   601   600       | 625   624   623       | 657   656   655       |
| Head Tube Length (mm)          | 95                    | 105                   | 120                   | 135                   |
| Head Tube Angle                | 63,1°   63,5°   63,9° | 63,1°   63,5°   63,9° | 63,1°   63,5°   63,9° | 63,1°   63,5°   63,9° |
| Fork Rake (mm)                 | 44                    | 44                    | 44                    | 44                    |
| Trail (mm)                     | 133,3   130,3   127,4 | 133,3   130,3   127,4 | 133,3   130,3   127,4 | 133,3   130,3   127,4 |
| Wheelbase (mm)                 | 1226   1226   1227    | 1261   1261   1261    | 1287   1288   1288    | 1323   1323   1323    |
| Chain Stay Length (mm)         | 450   450   450       | 450   450   450       | 450   450   450       | 450   450   450       |
| Bottom Bracket Drop (mm)       | 10   5                | 10   5                | 10   5                | 10   5                |
| Stack (mm)                     | 647   645   642       | 656   654   651       | 669   667   665       | 683   680   677       |
| Reach (mm)                     | 426   430   435       | 456   460   465       | 476   480   485       | 505   510   515       |
| Handlebar Width (mm)           | 800                   | 800                   | 800                   | 800                   |
| Stem Length (mm)               | 40                    | 40                    | 40                    | 40                    |
| Crank Length (mm)              | 160                   | 160                   | 160                   | 160                   |
| Wheel Size                     | R27.5" / F29"         | R27.5" / F29"         | R27.5" / F29"         | R27.5" / F29"         |

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση