REIGN ADVANCED E+ 1



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio
STEUEREINHEIT	Giant RideControl Ergo 4
DISPLAY	Giant RideControl Go Lux
AKKU	iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
CHARGER	Giant EnergyPak 4A Charger, 48V
RAHMEN	
RAHMEN	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
GABEL	Fox Float 38 Performance Elite, 180mm, GripX2 damper, 4-way adjust, 110x15, Kabolt X
DÄMPFER	Fox DHX Performance Elite, 205x65mm, LSC | LSR | Std Steel Spring custom tuned
KOMPONENTEN	
LENKER	Giant Contact SL TR35, 35mm rise, 5-degree upsweep, 9-degree backsweep, 35x800mm
GRIFFE	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
VORBAU	Giant Contact SL 35, 40 mm
SATTELSTÜTZE	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SATTEL	Giant Romero, neutral
ANTRIEB	
SCHALTHEBEL	SRAM Eagle 90 Transmission
SCHALTWERK	SRAM 90 Eagle Transmission
BREMSEN	TRP EVO Expert, hydraulic disc, 4-piston, 220mm rotors [F/R]
BREMSHEBEL	TRP EVO Expert
KASSETTE	SRAM Eagle Transmission, 10x52, 12-speed
KETTE	SRAM Eagle Transmission, Flattop, PowerLink, 12-speed
KURBEL	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

LAUFRÄDER	
FELGEN	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
NABE	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
SPEICHEN	Sapim Race [F] E-Lite [R], e-bike optimized
REIFEN	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
EXTRAS	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
BELEUCHTUNG	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

GEOMETRIEDATEN

RAHMEN	**S**	**M**	**L**	**XL**
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Sitzrohrwinkel	77.1° | 77.5° | 77.9°	77.5° | 77.9°	77.1° | 77.5° | 77.9°	77.1° | 77.5° | 77.9°
Oberrohrlänge (mm)	570 | 569 | 568	601 | 600	625 | 624 | 623	657 | 656 | 655
Steuerrohr-Länge (mm)	95	105	120	135
Steuerrohr-Winkel	63.1° | 63.5° | 63.9°	63.5° | 63.9°	63.1° | 63.5° | 63.9°	63.1° | 63.5° | 63.9°
Radstand (mm)	1226 | 1226 | 1227	1261 | 1261	1287 | 1288 | 1288	1323 | 1323 | 1324
Kettenstreben-Länge (mm)	450 | 450 | 450	450 | 450	450 | 450 | 450	450 | 450 | 450
Stack (mm)	647 | 645 | 642	654 | 651	669 | 667 | 665	683 | 680 | 678
Reach (mm)	426 | 430 | 435	460 | 465	476 | 480 | 485	505 | 510 | 514
Kurbellänge (mm)	155	155	155	155

Spezifikations-, Preis- und Farbänderungen vorbehalten.