

REIGN ADVANCED E+ 1



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Pro3, 48v, 90Nm, 800W max power, 400% max support ratio
COMMANDE	Giant RideControl Ergo 4
ECRAN	Giant RideControl GO Lux
BATTERIE	Giant EnergyPak Smart 560Wh, integrated, 48V
ENERGYPAK PLUS COMPATIBLES	Giant EnergyPak Plus 280 range extender compatible
CHARGEUR	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITÉ	Tire Checker Aegis, E-Lock, FindMyBike
CADRE	
TAILLES	S, M, L, XL
COLORIS	Mercury/Carbon Smoke
CADRE	Advanced-grade composite frame, Advanced forged composite upper rocker and internal link, 170mm Maestro suspension system
FOURCHE	Fox 38 Performance Elite, 29", 180mm travel, Grip X2 damper, 44mm offset, KaboltX 110x15mm Boost axle
AMORTISSEUR	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
COMPOSANTS	
CINTRE	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Giant Contact Switch adjustable dropper, 30,9mm (S:110-140, M:140-170, L/XL: 170-200) MMX remote
SELLE	Giant Romero, Neutral
DÉRAILLEUR	
MANETTES	SRAM Eagle 90 Transmission Single Click
DÉRAILLEUR ARRIÈRE	SRAM 90 Eagle Transmission
FREINS	TRP DH-R EVO, hydraulic disc, E2.3 caliper, 4-piston, 220mm [F/R]
LEVIER DE FREIN	TRP DH-R EVO
CASSETTE	SRAM Eagle Transmission, 10-52T, 12-speed
CHAÎNE	SRAM 70 Eagle Transmission Flattop Powerlink 12-speed
PÉDALIER	SRAM Eagle Transmission 36T chainring Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

ROUES	
JANTES	Giant e-TRA, Hookless, 30mm inner width, Hollow Side-Wall Design for improved strength and flat protection, 2~4psi lower air pressure recommended
MOYEURS	Giant e-TRA, E-Drive 260Nm 6-Pawl Driver, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
RAYONS	Giant TRA, Dynamic Balanced Lacing
PNEUS	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles (éclairages e-bike Recon disponible et directement connectable)

Prix Public Conseillé: 8 500,00 €

GÉOMÉTRIE

CADRE	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longueur de tube de selle (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	235			260			285			310		
Angle de tube de selle	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°		
Longueur du tube supérieur (mm)	570	569	568	602	601	600	625	624	623	657	65	
Longueur du tube de direction (mm)	95			105			120			135		
Angle du tube de direction	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	6	
Déport de fourche (mm)	44			44			44			44		
Trail (mm)	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4	133,3	1	
Empattement (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1323	1	
Longueur des bases (mm)	450	450	450	450	450	450	450	450	450	450	45	
Drop du boîtier de pédalier (mm)	10	5		10	5		10	5		10	5	
Stack (mm)	647	645	642	656	654	651	669	667	665	683	68	
Reach (mm)	426	430	435	456	460	465	476	480	485	505	51	
Largeur de cintre (mm)	800			800			800			800		
Longueur de potence (mm)	40			40			40			40		
Longueur des manivelles (mm)	160			160			160			160		
Diamètre des roues	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" /		

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.