

REIGN ADVANCED E+ 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Ergo 4
DISPLAY	Giant RideControl GO Lux
BATTERY	Giant EnergyPak Smart 560Wh, integrated, 48V
CHARGER	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
CADRU	
MARIMI	S, M, L, XL
CULORI	Mercury/Carbon Smoke
CADRU	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
FURCA	Fox 38 Performance Elite, 29", 180mm travel, Grip X2 damper, 44mm offset, KaboltX 110x15mm Boost axle
SOC	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
COMPONENTE	
GHIDON	Giant Contact SL TR35, 35x800mm, 35mm rize, Up: 5° Back: 9°
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
PIPA	Giant Contact SL 35
TIJA SA	Giant Contact Switch adjustable dropper, 30,9mm (S:110~140, M:140~170, L/XL: 170~200) MMX remote
SA	Giant Romero, Neutral
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM Eagle 90 Transmission Single Click
SCHIMBATOR SPATE	SRAM 90 Eagle Transmission
FRANE	TRP DH-R EVO, hydraulic disc, E2.3 caliper, 4-piston, 220mm [F/R]
MANETE FRANA	TRP DH-R EVO
PINIOANE	SRAM Eagle Transmission, 10-52T, 12-speed
LANT	SRAM 70 Eagle Transmission Flattop Powerlink 12-speed
ANGRENAJ	SRAM Eagle Transmission 36T chainring Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

ROTI	
JANTE	Giant e-TRA, Hookless, 30mm inner width, Hollow Side-Wall Design for improved strength and flat protection, 2~4psi lower air pressure recommended
BUTUCI	Giant e-TRA, E-Drive 260Nm 6-Pawl Driver, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
SPITE	Giant TRA, Dynamic Balanced Lacing
ANVELOPE	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAS	Aegis Tire Checker
ACCESSORIES	
LIGHTING	Optional: - Giant Recon series e-bike lights available and direct connectable

GEOMETRIE

CADRU	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	235			260			285			310		
Seat Tube Angle	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°
Top Tube Length (mm)	570	569	568	602	601	600	625	624	623	657	656	655
Head Tube Length (mm)	95			105			120			135		
Head Tube Angle	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4
Wheelbase (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1323	1323	1323
Chain Stay Length (mm)	450	450	450	450	450	450	450	450	450	450	450	450
Bottom Bracket Drop (mm)	10	5		10	5		10	5		10	5	
Stack (mm)	647	645	642	656	654	651	669	667	665	683	680	677
Reach (mm)	426	430	435	456	460	465	476	480	485	505	510	515
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	160			160			160			160		
Wheel Size	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

Toate specificatiile enumerate se pot schimba fara notificare prealabila.