



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
OVLÁDAČ	Giant RideControl Ergo 4
OVLÁDACIA JEDNOTKA	Giant RideControl GO Lux
BATÉRIA	Giant EnergyPak Smart 560Wh, integrated, 48V
NABÍJAČKA	Giant EnergyPak smart charger 4A, 48V
KONEKTIVITA	Aegis Tire Checker included in RideControl display
RÁM	
VELKOSTI	S, M, L, XL
FARBY	Mercury/Carbon Smoke
RÁM	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
VIDLICA	Fox 38 Performance Elite, 29", 180mm travel, Grip X2 damper, 44mm offset, KaboltX 110x15mm Boost axle
TLMIČ	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
KOMPONENTY	
RIADIDLÁ	Giant Contact SL TR35, 35x800mm, 35mm rize, Up: 5° Back: 9°
GRIPY	Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
PREDSTAVEC	Giant Contact SL 35
SEDLOVKA	Giant Contact Switch adjustable dropper, 30,9mm (S:110~140, M:140~170, L/XL: 170~200) MMX remote
SEDADLO	Giant Romero, Neutral
POHON	
RADENIE	SRAM Eagle 90 Transmission Single Click
PREHADZOVAČKA	SRAM 90 Eagle Transmission
BRZDY	TRP DH-R EVO, hydraulic disc, E2.3 caliper, 4-piston, 220mm [F/R]
BRZDOVÉ PÁKY	TRP DH-R EVO
KAZETA	SRAM Eagle Transmission, 10-52T, 12-speed
REŤAZ	SRAM 70 Eagle Transmission Flattop Powerlink 12-speed
KLUKY	SRAM Eagle Transmission 36T chainring Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

KOLESÁ	
RÁFIKY	Giant e-TRA, Hookless, 30mm inner width, Hollow Side-Wall Design for improved strength and flat protection, 2~4psi lower air pressure recommended
NÁBOJE	Giant e-TRA, E-Drive 260Nm 6-Pawl Driver, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
ŠPICE	Giant TRA, Dynamic Balanced Lacing
PNEUMATIKY	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
DOPLNKY	Aegis Tire Checker
PRÍSLUŠENSTVO	
OSVETLENIE	Optional: - Giant Recon series e-bike lights available and direct connectable

Cena: 8 299 €

GEOMETRIA

RÁM	S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	400			425			450		
Hĺbka vloženia sedlovky (mm)	235			260			285		
Uhol sedlovej trubky	77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1° 77,5° 77,9°		
Dĺžka hornej rámovej trubky (mm)	570 569 568			602 601 600			625 624 623		
Dĺžka hlavovej trubky (mm)	95			105			120		
Uhol hlavovej trubky	63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1° 63,5° 63,9°		
Offset vidlice (mm)	44			44			44		
Trail (mm)	133,3 130,3 127,4			133,3 130,3 127,4			133,3 130,3 127,4		
Rázvor (mm)	1226 1226 1227			1261 1261 1261			1287 1288 1288		
Dĺžka zadnej stavby (mm)	450 450 450			450 450 450			450 450 450		
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	10 5			10 5			10 5		
Stack - výška riadenia (mm)	647 645 642			656 654 651			669 667 665		
Reach (mm)	426 430 435			456 460 465			476 480 485		
Šírka riaditok (mm)	800			800			800		
Dĺžka predstavca (mm)	40			40			40		
Dĺžka kľúk (mm)	160			160			160		
Rozmer kolies	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.