

REIGN ADVANCED E+ 1

GIANT



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio
OVLÁDAČ	Giant RideControl Ergo 4
OVLÁDACIA JEDNOTKA	Giant RideControl Go Lux
BATÉRIA	iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
NABÍJAČKA	Giant EnergyPak 4A Charger, 48V
RÁM	
RÁM	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
VIDLICA	Fox Float 38 Performance Elite, 180mm, GripX2 damper, 4-way adjust, 110x15, Kabolt X
TLMIČ	Fox DHX Performance Elite, 205x65mm, LSC LSR Std Steel Spring custom tuned
KOMPONENTY	
RIADIDLÁ	Giant Contact SL TR35, 35mm rise, 5-degree upsweep, 9-degree backsweep, 35x800mm
GRIPY	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
PREDSTAVEC	Giant Contact SL 35, 40 mm
SEDLOVKA	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SEDADLO	Giant Romero, neutral
POHON	
RADENIE	SRAM Eagle 90 Transmission
PREHADZOVAČKA	SRAM 90 Eagle Transmission
BRZDY	TRP EVO Expert, hydraulic disc, 4-piston, 220mm rotors [F/R]
BRZDOVÉ PÁKY	TRP EVO Expert
KAZETA	SRAM Eagle Transmission, 10x52, 12-speed
REŤAZ	SRAM Eagle Transmission, Flattop, PowerLink, 12-speed
KLUKY	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

KOLESÁ	
RÁFIKY	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
NÁBOJE	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
ŠPICE	Sapim Race [F] E-Lite [R], e-bike optimized
PNEUMATIKY	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
DOPLNKY	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
PRÍSLUŠENSTVO	
OSVETLENIE	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITY	
COMBINED MAXIMUM LOAD LIMIT	156kg

Cena: 8 599 €

GEOMETRIA

RÁM	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Uhol sedlovej trubky	77,1°	77,5°	77,9°	77,5°	77,1°	77,5°	77,9°	77,1°
Dĺžka hornej rámovej trubky (mm)	570	569	568	601	600	625	624	623
Dĺžka hlavovej trubky (mm)	95		105	120		135		
Uhol hlavovej trubky	63,1°	63,5°	63,9°	63,5°	63,9°	63,1°	63,5°	63,9°
Rázvor (mm)	1226	1226	1227	1261	1261	1287	1288	1323
Dĺžka zadnej stavby (mm)	450	450	450	450	450	450	450	450
Stack - výška riadenia (mm)	647	645	642	654	651	669	667	665
Reach (mm)	426	430	435	460	465	476	480	485
Dĺžka klúku (mm)	155		155	155		155		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.