

REIGN ADVANCED E+ 1

GIANT



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio
TIPALO	Giant RideControl Ergo 4
PRIKAZOVALNIK	Giant RideControl Go Lux
BATERIJA	iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
CHARGER	Giant EnergyPak 4A Charger, 48V
OKVIR	
OKVIR	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
VILICE	Fox Float 38 Performance Elite, 180mm, GripX2 damper, 4-way adjust, 110x15, Kabolt X
AMORTIZER	Fox DHX Performance Elite, 205x65mm, LSC LSR Std Steel Spring custom tuned
KOMPONENTE	
KRMILO	Giant Contact SL TR35, 35mm rise, 5-degree upsweep, 9-degree backsweep, 35x800mm
GRIPS	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
OPORA KRMILA	Giant Contact SL 35, 40 mm
OPORA SEDEŽA	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SEDEŽ	Giant Romero, neutral
POGON	
PRESTAVNE ROČICE	SRAM Eagle 90 Transmission
ZADNJI MENJALNIK	SRAM 90 Eagle Transmission
ZAVORE	TRP EVO Expert, hydraulic disc, 4-piston, 220mm rotors [F/R]
ZAVORNE ROČICE	TRP EVO Expert
VERIŽNIK	SRAM Eagle Transmission, 10x52, 12-speed
VERIGA	SRAM Eagle Transmission, Flattop, PowerLink, 12-speed
GONILKE Z VERIŽNIKI	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

OBROČNIKI	
OBROČI	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
PESTA	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
NAPERE	Sapim Race [F] E-Lite [R], e-bike optimized
PLAŠČI	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
DODATKI	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
DODATNA OPREMA	
SVETILA	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW HIGH		LOW HIGH		LOW HIGH		LOW HIGH	
Kot sedežne cevi	77,1° 77,5°		77,9° 77,5°		77,9° 77,1°		77,5° 77,9°	
Top Tube Length (mm)	570 569		568 601		600 625		624 623	
Višina glave okvirja (mm)	95		105		120		135	
Krmilni kot	63,1° 63,5°		63,9° 63,5°		63,9° 63,1°		63,5° 63,9°	
Medosna razdalja (mm)	1226 1226		1227 1261		1261 1287		1288 1288	
Dolžina cevi ob verigi (mm)	450 450		450 450		450 450		450 450	
Oddaljenost zgornje cevi od gonilne osi (mm)	647 645		642 654		651 669		667 665	
Doseg (mm)	426 430		435 460		465 476		480 485	
Dolžina gonilke (mm)	155		155		155		155	

Vse navedene specifikacije se lahko spremenijo brez obvestila.