



СПЕЦИФИКАЦИИ

ХИБРИДНА ТЕХНОЛОГИЯ ЗА КОЛОЕЗДЕНЕ	
МОТОР	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
КОНТРОЛЕР	Giant RideControl Ergo 4
ДИСПЛЕЙ	Giant RideControl GO Lux
БАТЕРИЯ	Giant EnergyPak Smart 560Wh, integrated, 48V
ЗАРЯДНО	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
РАМКА	
РАЗМЕР	S, M, L, XL
ЦВЯТ	Moon Dust
РАМКА	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
ВИЛКА	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
ЗАДЕН АМОРТИСЬОР	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SL TR35, 35x800mm, 35mm rize, Up: 5° Back: 9°
ГРИПОВЕ	Giant Tactal Pro-E, tapered design, 135mm Ø28–30mm (S/M) 142mm Ø29–32mm (L/XL)
ЛАПА	Giant Contact SL 35
КОЛЧЕ ЗА СЕДАЛКА	Giant Contact Switch adjustable dropper, 30,9mm (S:110–140, M:140–170, L/XL: 170–200) MMX remote
СЕДАЛКА	Giant Romero, Neutral
DRIVETRAIN	
КОМАНДИ	Shimano Deore
ЗАДЕН ДЕРАЙЛЪОР	Shimano Deore, 12-speed shadow+
СПИРАЧКИ	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano SLX
КАСЕТА	Shimano Deore, 10-51T, 12-speed
ВЕРИГА	Shimano Deore 12-speed
КУРБЕЛ	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

КАПЛИ	
ШИНИ	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
ГЛАВИНИ	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
СПИЦИ	Sapim Race [F] E-Lite [R], e-bike optimized
ГУМИ	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
ЕКСТРИ	Aegis Tire Checker
АКСЕСОАРИ	
СВЕТЛИНИ	Optional: - Giant Recon series e-bike lights available and direct connectable

ГЕОМЕТРИЯ

РАМКА	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	235			260			285			310		
Seat Tube Angle	77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1° 77,5° 77,9°			77,1° 77,5° 77,9°		
Top Tube Length (mm)	570 569 568			602 601 600			625 624 623			657 656 655		
Head Tube Length (mm)	95			105			120			135		
Head Tube Angle	63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1° 63,5° 63,9°			63,1° 63,5° 63,9°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	133,3 130,3 127,4			133,3 130,3 127,4			133,3 130,3 127,4			133,3 130,3 127,4		
Wheelbase (mm)	1226 1226 1227			1261 1261 1261			1287 1288 1288			1323 1323 1323		
Chain Stay Length (mm)	450 450 450			450 450 450			450 450 450			450 450 450		
Bottom Bracket Drop (mm)	10 5			10 5			10 5			10 5		
Stack (mm)	647 645 642			656 654 651			669 667 665			683 680 677		
Обсер (mm)	426 430 435			456 460 465			476 480 485			505 510 515		
Ширина на Кормило (mm)	800			800			800			800		
Дължина на Лапа (mm)	40			40			40			40		
Дължина на Курбел (mm)	160			160			160			160		
Размер на Каплите	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

All specifications listed are subject to change without notice.