REIGN ADVANCED E+ 2



SPECIFIKATIONER

E+ SYSTEM	
MOTOR	Giant SyncDrive Pro3X,100Nm,48V 800W max power, 400% max support ratio
KONTROLLER	Giant RideControl Ergo 4
DISPLAY	Giant RideControl Go Lux
BATTERI	iant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
LADER	Giant EnergyPak 4A Charger, 48V
RAMME	
RAMME	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
FORGAFFEL	RockShox Zeb select, 29", 180mm travel, Delta RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
BAGDÆMPER	RockShox SuperDeluxe Select, RT, 205x65mm, custom tuned, 30% sag recommended
KOMPONENTER	
STYR	Giant Contact TR35, 35mm rize, Up: 5º Back: 9º, 35x800mm
GREB / STYRBÅND	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
FREMPIND	Giant Contact SL 35, 40 mm
SADELPIND	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SADEL	Giant Romero, neutral
GEARGRUPPE	
SKIFTEGREB	Shimano Deore, 12-speed
BAGSKIFTER	Shimano Deore, RD-7200,12-speed Shadow+
BREMSER	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F/R]
BREMSEGREB	TRP EVO Comp
KASSETTE	Shimano Deore, HyperGlide+, 12-speed, 11-51T
KÆDE	Shimano Deore, 12-speed
KRANKSÆT	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

HJUL	
FÆLGE	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
NAV	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
EGER	Sapim Race [F] E-Lite [R], e-bike optimized
DÆK	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
EKSTRA	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
TILBEHØR	
LYGTER	Optional: Giant Recon series e-bike lights available and direct-connect compatible
GRÆNSER	
KOMBINERET MAKSIMAL BELASTNINGSGRÆNSE	156kg

Pris: 55.579,00 kr.

GEOMETRI

RAMME	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Sadelrørsvinkel	77,1° | 77,5° | 77,9°	77,5° | 77,9°	77,1° | 77,5° | 77,9°	77,1° | 77,5° | 77,9°
Overrørslængde (mm)	570 | 569 | 568	601 | 600	625 | 624 | 623	657 | 656 | 655
Kronrørslængde (mm)	95	105	120	135
Kronrøsvinkel	63,1° | 63,5° | 63,9°	63,5° | 63,9°	63,1° | 63,5° | 63,9°	63,1° | 63,5° | 63,9°
Akselafstand (mm)	1226 | 1226 | 1227	1261 | 1261	1287 | 1288 | 1288	1323 | 1323 | 1324
Kædestagslængde (mm)	450 | 450 | 450	450 | 450	450 | 450 | 450	450 | 450 | 450
Stack (mm)	647 | 645 | 642	654 | 651	669 | 667 | 665	683 | 680 | 678
Reach (mm)	426 | 430 | 435	460 | 465	476 | 480 | 485	505 | 510 | 514
Pedalarmslængde (mm)	155	155	155	155

Alle de anførte specifikationer kan ændres uden varsel.